

## Technical Specification

Product Code: GM2004BK

Description: 20AX 2 Way Retractive Switch Module



## General Information

Dimensions (mm)	24.5 (W) x 50 (H) x 22.5 (D)
Finish	Black
Insert Colour	Black
Switch Finish	Black
Materials	Body & Insert: Nylon Terminals: Brass Contacts: Silver "on-lay" Copper / Brass
Anti Microbial Certified	No
Rated Voltage (V~) (Ue)	250
Inductive Load Rating (AX)	20
Load Rating Comments	Suitable for Inductive Loads
Termination Type	Screw
Terminal Size (mm)	Ø5
Terminal Capacity - Solid (mm <sup>2</sup> )	3 x 2.5 or 2 x 4
2 Way Switch	Yes
Retractive Contact Options	Press to Make or Break
Minimum Back Box Depth (mm)	25 (35 Flat Plate)
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +40
Warranty (Years)	10

Standards BS EN 60669-1

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

