

Product Code: GM2004BKBN

Description: 20AX 2 Way Retractive Switch Module



General Information

Dimensions (mm)	24.5 (W) x 50 (H) x 22.5 (D)		
Finish	Black Nickel		
Insert Colour	Black		
Switch Finish	Black Nickel		
Materials	Body & Insert: Nylon Switch Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated Spring: Spring Steel		
Anti Microbial Certified	No	Switch: Urea	
Rated Voltage (V~) (Ue)	250	Terminals: Brass	
Inductive Load Rating (AX)	20	Contacts: Silver "on-lay" Copper / Brass	
Load Rating Comments	Suitable for Inductive Loads		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Frequency (Hz)	50
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4	Terminal Torque Value (Nm)	1.2
2 Way Switch	Yes		
Retractive Contact Options	Press to Make or Break		
Minimum Back Box Depth (mm)	25 (35 Flat Plate)		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	10		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.