

Product Code: GM2047BKCH

Description: 13A Fused Connection Module


General Information

Dimensions (mm)	24.5 (W) x 50 (H) x 25 (D)	
Finish	Polished Chrome	
Insert Colour	Black	
Materials	Body & Insert: Nylon Internal Busbars: Brass Terminal Screws: Steel & Yellow Passivated	Insert Cover: Stainless Steel Terminals: Brass
Anti Microbial Certified	No	
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Fuse Fitted Rating & Type	13A (BS 1362)	
Termination Type	Screw	
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm²)	3 x 2.5, 2 x 4	
Product Marking	Fused Symbol	
Minimum Back Box Depth (mm)	25 (35 Flat Plate)	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	
Standards	BS 1363-4 BS 1362	

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.