



Betaduct narrow slot metric blue trunking.

Key features.

- Ideal for use with slimmer terminal blocks where more access is required
- Improves appearance of panels with cables out in best position
- Ideal for all panel building applications, also suitable for I.S circuits
- For use when bundles, cables and wires need supporting in control panels, distribution boards and switchgear
- Lightweight self extinguishing cable trunking with excellent rigidity and performance characteristics

Specification.

Material:
Rigid PVC

Operating temperatures:
-5 to +65°C

Density:
1.54

Dielectric strength:
15 kV/mm

Flammability:
UL94 V-0 rated material

Standards:
RoHS compliant

Colour:
Light blue
RAL 5015

Volume resistivity:
 $10^{15} \Omega \cdot \text{cm}$

Part no.	Nominal size outer (H x W) mm	Pack quantity (m)
104760032Y	30 x 25	48
104760024Y	40 x 25	48
104760034	40 x 30	48
104760044	40 x 40	24
104760036Y	60 x 30	24
104760046Y	60 x 40	16
104760066Y	60 x 60	24
104760086Y	60 x 80	24
104760038Y	80 x 30	16
104760048Y	80 x 40	16
104760068Y	80 x 60	16
104760088Y	80 x 80	16
104760610Y	100 x 60	16
1047601010Y	100 x 100	8
104760108Y	80 x 100	8
104760810Y	100 x 80	8