



Overview

Lead time	Usually Ships within 4 Weeks
-----------	------------------------------

Main

Range	ClimaSys
Product name	ClimaSys CV
Product or component type	Fan
Range compatibility	Prisma (P) Prisma (G)
Type of filter	Standard
Flow rate	Free flow rate with standard filter: 562 m ³ /h at 50 Hz Free flow rate with standard filter: 586 m ³ /h at 60 Hz
[Us] rated supply voltage	207...244 V
Input voltage	230 V 50/60 Hz

Complementary

Absorbed power	68 W 50 Hz 85 W 60 Hz
[In] rated current	0.52 A 50 Hz 0.37 A 60 Hz
Noise level < at	59 dB
Bearing type	Ball
Height	336 mm external:
Width	316 mm external:
Depth	161 mm external:
Cut-out dimensions	291 x 291 mm
Net weight	3.2 kg
Material	Outlet grille: injected thermoplastic (ASA PC)
Colour	Outlet grille: grey (RAL 7035)
Ambient air temperature for operation	-15...60 °C
Ambient air temperature for storage	-40...70 °C
Maximum pressure	140 Pa flow rate 0 m ³ /h
Connections - terminals	Terminal block
IP degree of protection	IP54

Device composition	1 axial motor 2 protective grille: on the front and rear surfaces 1 filter: front of axial motor 1 outlet grille: front 1 cut-out template
Condition of use	Filter must be cleaned and replaced regularly Surrounding environment must be relatively clean Outside temperature must be 5 °C lower than inside temperature Overfrequent filter replacement should be avoided Flow rates depends on the work point, see ProClima software

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23 cm
Package 1 Width	32 cm
Package 1 Length	34 cm
Package 1 Weight	3.554 kg
Unit Type of Package 2	P12
Number of Units in Package 2	24
Package 2 Height	119 cm
Package 2 Width	80 cm
Package 2 Length	120 cm
Package 2 Weight	120 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------