
Product data sheet Characteristics

NSYMR86

Monobloc perforated plates H800xW600mm with universal perforations 11x26mm





Overview

Lead time	Usually Ships within 4 Weeks	
-----------	------------------------------	--

Main

· · · · · · · · · · · · · · · · · · ·		
Range	Spacial	
Accessory / separate part category	Mounting accessory	
Product or component type	Mounting plate	
Device application	Multi-purpose	
Enclosure nominal dimensions	800 MmW: 600 mm 800 mmW: 1200 mm	
Mounting location	Step slide Direct fixing on backstuds	
Mounting plate description	Telequick perforated	
Range compatibility	Spacial (Spacial S3D) Spacial (Spacial CRN) Spacial (Spacial S3X) Thalassa (Thalassa PLM)	
Quantity per set	Set of 1	
Material	Steel	
Surface finish	Zinc coated	

Complementary

Fixing mode	Screwed on backstuds - screw type M8 By fixing element	
Height	750 mm	
Width	551 mm	
Depth	15 mm	
Thickness	2 mm	
Net weight	3.16 kg	
Number of slots	867	
Variant particularity	With enclosures H800 x W1200 Installation in rear of enclosure	
Cut-out dimensions	11 x 26 mm	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.0 cm
Package 1 Width	55.5 cm
Package 1 Length	75.5 cm
Package 1 Weight	3.18 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	126
Package 2 Height	90.0 cm
Package 2 Width	100.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	429.0 kg

Offer Sustainability

•	
Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months