



Main

Range	Masterpact
Range of product	MasterPact NW
Product or component type	Control unit
Trip unit name	Micrologic 5.0 H
Trip unit technology	Electronic
Range compatibility	Masterpact NW08...40 Masterpact NW40b...63 Masterpact NW H10 Masterpact NW H2 corrosion protection
Device application	Distribution
Number of poles	4P 3P
Protected poles description	4t 3t 3t + N/2
Trip unit protection functions	Selective protection
Protection type	For short time short-circuit protection For overload protection (long time) For instantaneous short-circuit protection
Trip unit rating	800 A at 50 °C 1000 A at 50 °C 1250 A at 50 °C 1600 A at 50 °C 2000 A at 50 °C 2500 A at 50 °C 3200 A at 50 °C 4000 A at 50 °C 5000 A at 50 °C 6300 A at 50 °C
Network type	AC
Network frequency	50/60 Hz
Circuit breaker mounting mode	Drawout

Complementary

Long-time pick-up adjustment type I _r (thermal protection)	Adjustable 9 settings
[I _r] long-time protection pick-up adjustment range	0.4...1 x I _n
Long-time protection delay adjustment type t _r	Adjustable 9 settings
[t _r] long-time protection delay adjustment range	0.7...16.6 S at 7.2 x I _r 0.7...24 S at 6 x I _r 12.5...600 s at 1.5 x I _r
Thermal memory	20 mn
Short-time protection pick-up adjustment type I _{sd}	Adjustable 9 settings
[I _{sd}] Short-time protection pick-up adjustment range	1.5...10 x I _r
Short-time protection delay adjustment type t _{sd}	Adjustable
[t _{sd}] Short-time protection delay adjustment range	0...0.4 S I _r ² t=off 0.1...0.4 s I _r ² t=on
Instantaneous protection pick-up adjustment type I _i	Adjustable 9 settings
[I _i] instantaneous protection pick-up adjustment range	2...15 x I _n Off
Earth-leakage protection	Without
Zone selective interlocking ZSI	With

Local signalling	3 LEDs (red) for electrical fault 1 LED (red) for internal error
Display type	Digital display
Type of measurement	Harmonics meter Power meter
Communication of data	Measurement readout Protection and alarm settings Maintenance indicators

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.0 cm
Package 1 Width	8.0 cm
Package 1 Length	22.0 cm
Package 1 Weight	1.117 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------