



## Main

Range	Lisse
Aesthetic name	White moulded
Product or component type	Switched socket
Device presentation	Complete product
Outlet standard	British
Colour tint	Matt white
Quantity per set	Set of 10
Type of packing	Carton

## Complementary

Switch function	2-pole
Rated current	13 A at 250 V AC 50 Hz
Actuator	Rocker
Number of gangs	1 gang
Fixing mode	By screws
Connections - terminals	Screw terminals
Material	Urea (carbamide)
Type of installation	Indoor
Depth	33 mm
Width	87 mm
Height	87 mm
Net weight	0.092 kg

## Environment





Standards	BS 1363-2
IP degree of protection	IP20

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	95 g
Package 1 Height	3.3 cm
Package 1 Width	8.7 cm
Package 1 Length	8.7 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	1.05 kg
Package 2 Height	9.5 cm
Package 2 Width	15.5 cm
Package 2 Length	18.4 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	200
Package 3 Weight	21.69 kg

Package 3 Height	33 cm
Package 3 Width	38.5 cm
Package 3 Length	49.5 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	 <a href="#">End Of Life Information</a>

### Contractual warranty

Warranty	18 months
----------	-----------