



## Main

Range	Lisse
Aesthetic name	White moulded
Product or component type	Switched socket
Device presentation	Complete product
Outlet standard	British
Colour tint	Matt white
Quantity per set	Set of 5
Type of packing	Carton

## Complementary

Switch function	2-pole
Rated current	13 A at 250 V AC 50 Hz
Actuator	Rocker
Number of gangs	2 gangs
Pilot light	Without LED
Fixing mode	By screws
Connections - terminals	Screw terminals
Material	Urea (carbamide)
Type of installation	Indoor
Depth	36 mm
Width	149 mm
Height	87 mm
Net weight	0.157 kg

## Environment

Standards	BS 1363-2
IP degree of protection	IP20

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	158.0 g
Package 1 Height	3.0 cm
Package 1 Width	8.5 cm
Package 1 Length	14.5 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Weight	878.0 g
Package 2 Height	9.5 cm
Package 2 Width	15.5 cm
Package 2 Length	16.5 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------