

Product data sheet

Characteristics

GGBL5011

Lisse - Fuse connection unit - LED - 1 gang - 13 A - white moulded



Main

Range	Lisse
Aesthetic name	White moulded
Product or component type	Fuse connection unit
Device presentation	Complete product
Colour tint	White moulded
Quantity per set	Set of 10

Complementary

Pilot light	LED
Actuator	Rocker
Number of gangs	1 gang
Material	Urea (carbamide)
Device mounting	Wall mounted
Fixing mode	By screws
Rated current	13 A at 250 V AC
Connections - terminals	Screw terminals
Type of packing	Carton
Width	87 mm
Height	87 mm
Depth	28 mm
Net weight	0.105 kg

Environment

Standards	BS 1363
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	105.71 g
Package 1 Height	3 cm
Package 1 Width	9 cm
Package 1 Length	9 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	1.144 kg
Package 2 Height	9.5 cm
Package 2 Width	15.5 cm
Package 2 Length	18.5 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	100

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Package 3 Weight	11.925 kg
Package 3 Height	17 cm
Package 3 Width	39.5 cm
Package 3 Length	49 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------