

## TRA250VAO 230-240/24 TRANSFORMER

| TYPE | Double Wound & Earth Screen |
|------|-----------------------------|
|------|-----------------------------|

|                                 |                       |
|---------------------------------|-----------------------|
| Loading/ Running Cyle           | CONTINUOUS            |
| VA Rating                       | 250VA                 |
| Input Voltage                   | 230-240V              |
| Input AMP Load                  | 1.04A                 |
| Output Voltage                  | 24V AC                |
| Output AMP Load                 | 10.41A                |
| Incoming Protective Devices     | N/A HARDWIRED         |
| Outgoing Protective Devices     | N/A HARDWIRED         |
| Input Auxiliary (App Inlet etc) | SCREW TERMINALS       |
| Output Auxiliary (Sockets etc)  | SCREW TERMINALS       |
| Frequency                       | 50/60 Hz              |
| Cooling                         | DRY- AIR COOLED       |
| Insulation                      | CLASS F               |
| Enclosure Type                  | N/A                   |
| Dimensions                      | 125x120x104mm (H,L,D) |
| Weight                          | 4kg                   |



*\*All images used for illustrative purposes only*



Page 1 of 2



# TRA250VAO 230-240/24

## TRANSFORMER

TYPE Double Wound & Earth Screen

### Additional items

N/A



*\*All images used for illustrative purposes only*

### Notes



Page 2 of 2

A TRADING DIVISION OF  
**CEE NORM**  
U.K. Ltd

Reg No. 2581049 (England & Wales)  
Reg. Office: Unit 2 Highbridge  
Court, Stafford Park 1, Telford,  
Shropshire, TF3 3BD



0161 336 7111  
01952 212700



[www.transpowerengineering.co.uk](http://www.transpowerengineering.co.uk)  
[www.ceenorm.co.uk](http://www.ceenorm.co.uk)



[sales@transpowerengineering.co.uk](mailto:sales@transpowerengineering.co.uk)  
[sales@ceenorm.co.uk](mailto:sales@ceenorm.co.uk)

