

Channel Timers

The KingShield 2 & 4 channel central heating & hot water timers offer the equivalent of 4 or 2 separate 7 day timers in one slim, elegant enclosure. Each channel offers up to 3 programmed operating periods with a boost and advance available on each.

- Up to 4 independently programmable channels (T634A-C)
- 40 on and off settings available per channel
- One hour boost facility for each channel
- Programme advance function for each channel
- Summertime setting
- 7 day battery back up
- Clear backlit LED display
- All products are individually clammed for ease of display

Technical Data

Voltage 230V AC, 3A resistive, 1.25A inductive per channel
Conforms to IEC 60730-2-7 and IEC 60730-1

	Part No	Description	Dimensions
	T612A-C	1 or 2 Channel Timer	H95 x W154 x D37mm
	T634A-C	1 - 4 Channel Timer	

Timer Socket

The KingShield 24hr mechanically timer socket simply replaces your normal socket, with the added benefit of a timer application. It has 96 on/off settings for maximum flexibility. Suitable for use with any 13A appliance you need to automatically control.

- On/off/timed selector
- Power consumption 0.9W
- Operation temperature -5°C to + 40°C

Technical Data

Voltage 230V AC - 50Hz, 13 Amp (4A inductive)
Conforms to BS 1363-2, EN 60730, EN 60730-2-7

	Part No	Description	Product Information/ Dimensions
	TS70A-C	24hr Mechanically 13A Timer Socket (IP66 Weatherproof version available PXC70TSKT-C p25)	96 on/off settings Operates with 15 minute on/off segments H87 x W147 x D14mm