

JC71744EM

Skypack QR LED batten 5ft twin IP20 62W 4000K 7200lm EM



Features & Benefits

Intelligent press release buttons for simple installation

Ultra efficient, up to 120 lumens per circuit Watt

Suitable for temperatures -10°C to 50°C

Press fit terminals, loop in loop out

Rear and end conduit entry points

Suspended LED tray for easy installation

General Information

Product Group	LED - Surface
Product Range	Skypack
Trade Name	Skypack
Light Source	LED

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross

Trading Estate, Bognor Regis, West Sussex, PO22 9TS

Company Registration Number: 03044848 | VAT Number: 918544112

T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk

Light Source Features	Neutral White
Lighting Product Type	Linear Lighting
Lighting Product Type	Emergency Lighting
Product Shape	Rectangular
Mounting	Surface Mounted
Product Weight	2.72kg
Color Finish	White
Overall Dimensions	1523 x 70 x 76.5
Recommended Product Location	Domestic, Commercial and Industrial Applications
Method Of Fix	Surface with Conduit Entry
IP Rating	IP20
Environment	Indoor
Origin Of Manufacture	Made In China
Guarantee	3 years
Driver Manufacturer	Ledtu
LED Manufacturer/Type	Runlite

Electrical

Voltage Rating	220-240
Secondary Running Current	1400mA
Primary Running Current	350mA
Operating Frequency (Hz)	50/60Hz
CC or CV	Constant Current
Luminaire Circuit Wattage	60W
Sec - Voltage (V)	27-40VDC
Class	Class I: requires an Earth connection

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross
Trading Estate, Bognor Regis, West Sussex, PO22 9TS
Company Registration Number: 03044848 | VAT Number: 918544112
T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk

EMC Compliant (EN55015)	Yes
Power Factor Correction	0.9
Input Electrical Connections	Live, Earth & Neutral
Dimmable	No

Emergency Data

Load Voltage	6-60VDC
Nominal Battery Current	1.2 Amp
Recharge Time	24 hours
Battery Specification	3.6V 4000mAH Ni-Cd
Battery Life In Emergency Mode	3 hours
Charge Current	140mA
DDP Protection	Yes, 2.8V
LOR In Emergency Mode	8-12%
Inverter PFC	0.8

Thermals

Room Ambient Temperature Not To Exceed	30°C
---	------

Performance Data

Energy Rating	A+
Actual Lumen Output	7200
Lumen Output	5001-8000
Lumens Per Circuit Watt	120
LED Life (Hours)	36000
Color Rendering Index	80-89

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross
Trading Estate, Bognor Regis, West Sussex, PO22 9TS
Company Registration Number: 03044848 | VAT Number: 918544112
T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk

CRI: Ra	80
Correlated Color Temperature	4000K
Light Distribution Detail	120-degree
LOR (Light Output Ratio) %	100
Photometry Available	Yes

Construction

Primary Material	Steel
Diffuser	Polycarbonate

Packaging

Quantity Per Outer Carton	8
Bar Code EAN Number	5052544080524
Packaged Weight	3.17kg

Standards & Approvals

Listings	CE
Manufactured In Accordance To	BS EN 60598:2015, 2-1, 2-22
CE Marked	Yes
Batch Coded	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Yes: available on request.
Accredited Members	LIA, ISO9001:2015, ISO14001:2015

Datasheet generated from <https://www.electrika.cloud> on 10 September 2018 14:31:52

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross
Trading Estate, Bognor Regis, West Sussex, PO22 9TS
Company Registration Number: 03044848 | VAT Number: 918544112
T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk