



Grommets - Quick Fit Type



Part Number	Description	A	B	C	D	E	F	Pack Qty
QGROMQ20OPEN	Black Quick Fit Open Cable Grommets 20mm	23.6mm	16.2mm	19.9mm	8.4mm	2.1mm	4.4mm	100
QGROMQ25OPEN	Black Quick Fit Open Cable Grommets 25mm	29.5mm	20.4mm	24.6mm	8.6mm	2.1mm	4.1mm	100
QGROMQ20CLOSED	Black Quick Fit Closed Cable Grommets 20mm	24.7mm	16.6mm	19.8mm	7.9mm	2.8mm	3.5mm	100
QGROMQ25CLOSED	Black Quick Fit Closed Cable Grommets 25mm	29.6mm	20.6mm	24.9mm	8.8mm	2.8mm	3.4mm	100


Grommets - Standard Type



Part Number	Description	A	B	C	D	E	Pack Qty
QGROM20OPEN	Black Open Cable Grommets 20mm	23.2mm	16.2mm	19.6mm	6.7mm	2.1mm	100
QGROM25OPEN	Black Open Cable Grommets 25mm	29mm	20mm	25.1mm	7.3mm	2.4mm	50
QGROM20CLOSED	Black Closed Cable Grommets 20mm	22.1mm	15.7mm	19.8mm	5.5mm	1.4mm	100
QGROM25CLOSED	Black Closed Cable Grommets 25mm	29.6mm	18.8mm	25.2mm	6.5mm	2mm	50

Earth Clamps

- Tested and approved to BS951



Part Number	Description	Pack Qty
QEC14	Earth Clamps EC 14 Dry Conditions	20
QEC15	Earth Clamps EC 15 Wet Conditions	20

Terminal Blocks

- PE material
- Brass insert
- Captive screw



Part Number	Description	Pack Qty
QTB5	Clear 5 Amp 12 Way Terminal Block Strips	10
QTB15	Clear 15 Amp 12 Way Terminal Block Strips	10
QTB30	Clear 30 Amp 12 Way Terminal Block Strips	10

Push in Connectors

Terminal Capacity: 0.5mm²-2.5mm² Stranded or Solid Core
Operating Temperature (Max.): 110°C



Part Number	Description	Pack Qty
QP2242Y	24A 450V Yellow Transparent 2 Port Push In Wire Connectors	100
QP3242O	24A 450V Orange Transparent 3 Port Push In Wire Connectors	100
QP4242T	24A 450V Transparent 4 Port Push In Wire Connectors	75
QP5242B	24A 450V Blue Transparent 5 Port Push In Wire Connectors	50
QP6242P	24A 450V Purple Transparent 6 Port Push In Wire Connectors	50
QP8242B	24A 450V Black Transparent 8 Port Push In Wire Connectors	40

PVC Tapes

General purpose non-migratory plasticised insulation tape supplied in lengths of 20m and 33m with all colours as detailed.

Tested for: Thickness, Tensile Elongation, Adhesion, Adhesion to Backing, Flagging, Corrosive Sulphur, Flame Propagation (CAT 2), Plastic to 31/90 (PVCP), Working Temperature up to 80°C.

- Made from self extinguishing flame retardant PVC
- Manufactured to comply with BS EN 60454-3
- Ideal for electrical binding, colour coding and identification



Part Number	Colour	Length	Width	Pack Qty
1920B	Black	20m	19mm	10
1920BL	Blue	20m	19mm	10
1920BR	Brown	20m	19mm	10
1920GR	Green	20m	19mm	10
1920GY	Grey	20m	19mm	10
1920R	Red	20m	19mm	10
1920W	White	20m	19mm	10
1920Y	Yellow	20m	19mm	10
1920YG	Yellow/Green	20m	19mm	10
1920MX01	Mixed Phase Colours (10 Pack) (2 x Black, Brown, Blue, Grey, Yellow/Green)	20m	19mm	1
1920MX02	Mixed Colours (10 Pack) (2 x Black, Brown, White & 1 x Red, Blue, Yellow, Yellow/Green)	20m	19mm	1

1933B	Black	33m	19mm	10
1933BL	Blue	33m	19mm	10
1933BR	Brown	33m	19mm	10
1933GR	Green	33m	19mm	10
1933GY	Grey	33m	19mm	10
1933R	Red	33m	19mm	10
1933W	White	33m	19mm	10
1933Y	Yellow	33m	19mm	10
1933YG	Yellow/Green	33m	19mm	10

Specialist Tapes

Part Number	Description	Length	Pack Qty
QUGT100X200	Underground Warning Tape 100mm x 200m Roll	200m	1
QDT50X50	Duct Tape 50mm x 50m Roll	50m	1

