

BCAB-L 17-20 BK LED Connection Pack

Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Type	BCAB-L 17-20 BK LED Connection Pack
WISKA-Order no.	10110226

Description:

BC-KIT 1 Includes:

2 x EBFS 17-20/ 1 x COMBI 206/ 1m BCAB-L 17/ 1 x ESKV 20+/ 1 x EMUG 20

Technical description of components:

EBFS 17-20 - Material number 10106867

Material Conduit fitting polyamide UL94-V0

Material Connection thread polyamide UL94-V0

Material sealing gasket TPU

Protection class IP66, IP68

Temp. range min -40 °C

Temp. range max 100 °C

Operational areas EN 45545 - Railway

NW 17

Thread type M

Ø Connection thread D 20

Lead 1,5

Length screw-in thread L 12 mm

Ø closure VD 32,7 mm

Ø inside 14,8 mm

Key width SW 27 mm

Total length TL 41,5 mm

Type of conduit fitting straight

UL 1696 Yes

Product Color RAL 9005

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk

COMBI 206 - Material number 10109571

Material Polypropylene
Material sealing gasket TPE
Temp. range min -30 °C
Temp. range max 100 °C
Temperatures during install. -5 °C - 60 °C
Protection class IP66 / IP67
Glow wire test 750 °C
Voltage 400 V
Rated cross section 1,5 mm²
Fixing 4 internal openings
Ø cable diameter min 3 mm
Ø cable diameter max 12 mm
External dimensions LxWxH 85 x 49 x 51mm
Using for cable gland Using for cable gland
Product Color RAL 9005

BCAB-L 17 - Material number 10109185

Material PA6 UL94-HB
Temp. range min -40 °C
Temp. range max 140 °C
Product Color RAL 9005
NW 17
External diameter ED 21,2 mm
Ø inside 16,8 mm
Profile width A 3,3 mm
Width B 2,3 mm
Bending radius R 50 mm
Wall thickness S 0,3 mm
Model light

ESKV 20+ - Material number 10100825

Material cable gland Polyamide
Material sealing gasket EPDM
Protection class IP69, IP68 (5 bar 30 min)
Temp. range min -40 °C
Temp. range max 100 °C
Glow wire test 750 °C
Thread type M
Ø Connection thread D 20
Lead 1,5
Length screw-in thread L 10 mm
Ø cable diameter min 7,5 mm
Ø cable diameter max 14 mm
Ø cable diameter UL 7,5 mm - 14 mm
Key width SW 24 mm
Collar diameter (E) 27 mm

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk

Total length TL 36 mm - 45 mm

Type of cable anchorage A

Install. torques fitting 4 N/m

Install. torques cap nut 3 N/m

Impact category 2

EMUG 20 - Material number 10061782

Material Polyamide, fibre reinforced

Temp. range min -40 °C

Temp. range max 100 °C

Glow wire test 650 °C

Thread type M

Ø Connection thread D 20

Lead 1,5

Key width SW 27 mm

Collar diameter (E) 29 mm

Total length TL 5 mm

Product Color RAL 9005

06.10.2021

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk

Other technical data on request / subject to change without notice