

KSRFRD383 – 5w output Compatible Dimmers

	Result	Observation	Acoustics	Qty	Comments
Dimmer	✓	100-10% Smooth Dim, dimming below 10% can cause flicker	Acoustic rating – 1	Up to 10	Recommended*
	✓	100-10% Smooth Dim	Acoustic rating – 1	Up to 10	Recommended
	✓	100-5% Incremental Dim	Acoustic rating – 1	Up to 10	Recommended*
	✓	100-0% Smooth Dim, dimming below 10% can cause flicker	Acoustic rating – 1	Up to 10	Recommended
	✓	100-15% Smooth Dim, dimming below 15% can cause flicker	Acoustic rating – 1	Up to 10	Recommended*
	✓	100-5% Smooth Dim, dimming below 10% can cause flicker	Acoustic rating – 1	Up to 10	Recommended*
	✓	100-15% Smooth Dim, dimming below 15% can cause flicker	Acoustic rating – 1	Up to 10	Recommended*
	✓	100-0% Smooth Dim, dimming below 15% can cause flicker	Acoustic rating – 1	Up to 10	Recommended
	✓	100-0% Smooth Dim, dimming below 15% can cause flicker	Acoustic rating – 2	Up to 10	Recommended
	✓	100-10% Smooth Dim if fittings are powered off at 25% dimmer will not power lights back on until dimming level increased	Acoustic rating – 1	Up to 10	Recommended
	✓	100-10% Smooth Dim if fittings are powered off at 25% dimmer will not power lights back on until dimming level increased	Acoustic rating – 2	Up to 10	Recommended
	✓	100-10% Smooth Dim	Acoustic rating – 1	Up to 10	Recommended
	✓	100-10% incremental Dim	Acoustic rating – 1	Up to 10	Recommended

Please Note: KSR test these dimmers singularly please consult the dimmer manufacturer for recommendations on other scenarios.
All recommendations are correct as per the date tested below. KSR cannot be held responsible for any changes in the dimmer specification.

1 – low to no Audible Noise 2 – Moderate audible Noise 3- High Audible Noise

*Acoustic Rating

Tested & Approved – November 2020