DOWNLIGHTS

ULTIMUM+ LED FIRE RATED











CONSTRUCTION:

- Die-cast aluminium heatsink
- protectors

- · Dimmable with selected trailing & leadingedge dimmers. Dimmer compatibility list
- ROBUS 3 pole connector with two push-in
- Colour temperature selectable; switch front of the fitting behind trim allows selection between 2700/3000/4000/6000K
- Fire Tested fo use in 30min/60min/90min Solid Timber Joists
- Fire, Moisture and Acoustic rating tested













220 240 OPERATING

0P











RUL07X4-01

50W halogen
6.5/6.4/6.3/6.5
510/550/590/580
80/86/95/91
440/460/490/460
2700/3000/4000/6000
80
0.9
0.32
40









Polished Chrome

Matt Black

Scan here for more product

Brushed Chrome

- Polycarbonate trim and LEDchroic lens optic
- Pressed steel and polycarbonate body
- Spring steel ceiling fixing springs with PVC

FEATURES:

- available on the website
- spring terminals per pole and cable restraint
- Tested for use with I-Joists & Metal Web Joists

DIMENSIONS(mm)	Diameter	Depth	Cut-out	Proj.
RI II 07X/-01	85	60	72	5

ACCESSORIES

RULSTRIM-03	ULTIMUM+ Polished Chrome Trim
RULSTRIM-10	ULTIMUM+ Matt Black Trim
RULSTRIM-13	ULTIMUM+ Brushed Chrome Trim
RI A400DT	LOADPRO 150W LED Dimmer



CONVERSIONS AVAILABLE



