DOWNLIGHTS

ULTIMUM TILT+ LED FIRE RATED











CONSTRUCTION:

- Polycarbonate trim and LEDchroic lens optic
- Die-cast aluminium heatsink
- Pressed steel and polycarbonate body
- Spring steel ceiling fixing springs with PVC protectors

FEATURES:

- 25° tilt versions
- Dimmable with selected trailing and leadingedge dimmers. Dimmer Compatibility List available on the website
- Colour temperature selectable; switch on the back of the fitting allows selection between 2700/3000/4000/6000K
- Fire Tested fo use in 30min/60min/90min Solid Timber Joists
- Tested for use with I-Joists & Metal Web Joists
- Fire, Moisture and Acoustic rating tested
- ROBUS 3 pole connector with two push-in spring terminals per pole and cable restraint























WARRANTY

RATED

LUMENS

RATED

IP RATING

CCT

RULT06X4-01

50W halogen
5.7/5.7/5.6/5.7
530/560/610/600
93/100/111/106
400/430/470/460
2700/3000/4000/6000
80
0.9
0.32
40





Brushed Chrome



Scan here for more product information

DIMENSIONS (mm) Diameter Depth Cut-out Proj RULT06X4-01 85 70 72 4

ACCESSORIES

RULTTRIM-13 ULTIMUM TILT+ Brushed Chrome Trim LOADPRO 150W LED Dimmer RLA400DT



CONVERSIONS AVAILABLE





ROBUS.COM 149