



Main

| | |
|---------------------------------|--|
| Circuit breaker application | Distribution |
| Range | Acti9 |
| Product name | Acti9 iC60 RCBO |
| Product or component type | Residual current breaker with overcurrent protection (RCBO) |
| Device short name | IC60H RCBO PoN |
| Poles description | 1P + N _s |
| [I _n] rated current | 10 A at 50 °C |
| Earthing system | TN |
| Curve code | C |
| Earth-leakage sensitivity | 30 mA |
| Breaking capacity | 10000 A I _{cn} at 240 V AC 50/60 Hz conforming to IEC 61009-2-2 |

Complementary






| | |
|---|---|
| Neutral position | Left |
| Number of protected poles | 1 |
| Device location in system | Outgoer |
| Network type | AC |
| Network frequency | 50/60 Hz |
| [U _e] rated operational voltage | 240 V AC 50/60 Hz |
| Trip unit technology | Thermal-magnetic |
| Magnetic tripping limit | 5...10 x I _n |
| Residual current tripping technology | Voltage dependent |
| Earth-leakage protection time delay | Instantaneous |
| Earth-leakage protection class | Type A |
| [I _{cs}] rated service breaking capacity | 7500 A at 240 V AC 50/60 Hz conforming to IEC 61009-2-2 |
| Electrical insulation class | Class II |
| Limitation class | 3 |
| [U _i] rated insulation voltage | 400 V AC 50/60 Hz |
| [U _{imp}] rated impulse withstand voltage | 4 kV |
| Surge current | 250 A |
| Suitability for isolation | Yes |
| Contact position indicator | Yes |
| Control type | Toggle |
| Local signalling | Fault indication ON/OFF indication |

| | |
|--|--|
| Mounting mode | Plug-on |
| Mounting support | Isobar A Isobar B |
| Comb busbar and distribution block compatibility | NO |
| 9 mm pitches | 2 |
| Height | 110 Mm |
| Width | 18 Mm |
| Depth | 72 Mm |
| Net weight | 156 G |
| Colour | White |
| Mechanical durability | 20000 Cycles |
| Electrical durability | 5000 Cycles |
| Locking options description | Padlock in on or off position |
| Connections - terminals | Screw clamp terminal (top) 1...16 mm² flexible Screw clamp terminal (bottom) 1...10 mm² flexible Screw clamp terminal (top) 1...25 mm² rigid Screw clamp terminal (bottom) 1...16 mm² rigid Plug-on neutral (upstream) |
| Wire stripping length | 14 Mm for top connection 13 Mm for bottom connection |
| Tightening torque | 3.5 N.M top 2 N.M bottom |
| Earth-leakage protection | Integrated |

Environment

| | |
|---------------------------------------|--|
| Standards | IEC 61009-2-2 IEC 61009-1 BS EN 61009-1 |
| Product certifications | CB |
| IP degree of protection | IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529 |
| Overvoltage category | II |
| Tropicalisation | 2 |
| Relative humidity | 95 % at 55 °C |
| Ambient air temperature for operation | -15...60 °C |
| Ambient air temperature for storage | -40...85 °C |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| China RoHS Regulation |  China RoHS Declaration |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile |  End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **Commercialised**