TECHNICAL SPECIFICATION



M600 Series - M632 - Box of 10 - FFP3V - MOULDED DISPOSABLE DUST MASK

M632 - - FFP3V - MOULDED DISPOSABLE DUST MASK / BGZ130-000-A00



DESCRIPTION

Moulded disposable respirator with comfort foam surround, adjustable nose clip, four-point adjustable harness and low resistance exhalation valve.

OPTIONS

M632 - - FFP3V - MOULDED DISPOSABLE DUST MASK (BGZ130-000-A00)

SAFETY STANDARDS

EN 149















SPECIFICATIONS

Classification

FFP3 (Filtering Facepiece Particulate, Valved)

Usage

NR (Non-Reusable)

Minimum Filtration Efficiency 99% For FFP3 Rated

Nominal Protection Factor

50

Mask Design

Moulded

4 Point Harness adjustment system

Yes

Latex free

Yes

Filter Shelf Life

5 Years



Filter Type

P (Protects Against Solid and Liquid Aerosols)



Activated Carbon Layer

No

Maximum Total Inward Leakage (TIL)

2%

UK Assigned Protection Factor

20



Exhalation Valve

Yes - Polystyrene exhalation valve with rubber diaphragm



Nose Bridge

Moulded in mask

Mask Material Polypropylene



Product Weight

22g (Approx) Each Mask

FEATURES



Exhalation Valve

Low resistance exhalation valve for easy breathing.



4-Point Adjustable Straps

Metal free, 4-point adjustable straps create a firm and adaptable fit.



Foam Padded Nose Bridge

A mouldable nose bridge and 360° foam area around the inside provide comfort and a firmer fit.

RANGE



DOWNLOADS

Image Pack (ZIP)

doc-m632.pdf (PDF)

doc-m632.pdf (PDF)







Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





