



Actual

Catalog Number: S50/10M
Product ID: 7TCA296010R0154
EAN Number: 05020963003677
Status: Active

Inherent Low Fire Hazard Steel Conduit, Nominal Conduit Size 50mm, Outside Diameter 53.0mm, Inside Diameter 48.4mm, Static Bend Radius 90mm, Reel Length 10 Meters, Galvanised Steel General Purpose

- Very high UV resistance
- High flexibility
- High fatigue life
- High mechanical strength
- Inherent low fire hazard and halogen free
- Lighting/Cable Track
- Under floor Wiring
- Light Industrial

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5535 Electrical conduit
Brand Name	Adaptaflex
Type	Low Fire Hazard Conduit
Special Features	Very High UV Protection and Fatigue Life
Application	Indoors / Outdoors - Light Industrial, Buildings
Trade Size	1-1/2 Inch
Outside Diameter	53.0mm
Inside Diameter	48.4mm
Length	10 m
Radius	90mm
Flexibility	Very High
Material	Galvanized Steel

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	50mm
Outer diameter	53mm
Inner diameter	48.4mm
Material	Steel
Surface protection	Other
Sheathing material 1st coating	Not sheathed
Operating temperature	-50-+300°C
Degree of protection (IP)	IP40
Weight	0.939kg/m
Colour	Metallic
Bending strength	Flexible

Packaging

Outer Quantity	1
Outer Dimensions (inches)	17x37x17
Weight Uom	20.7 lbs. Each

Header

3D Model	Available on Website
----------	----------------------

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com