

MINI-MAX

LED Bulkhead

FernHoward
Lighting



Highly energy efficient and vandal resistant, the Mini-Max is IP65 rated with a screwed down polycarbonate diffuser and rigidly constructed polycarbonate base.

IP65

IK10

LED

Lighting
CONTROL
Options

up to
139
lm/w

50,000
Hours
L70

>80
CRI (Ra)

4000K
Colour
Temperature

FEATURES

- Energy efficient LED gear tray
- IP65 – PU foam gasket protects against dust and water
- Smooth external edges for vandal resistance and easy cleaning
- Robust Polycarbonate body in black or white
- Clear or opal polycarbonate diffuser
- Retained diffuser screws
- Security screws available
- Available with all standard light management options

SIMPLE TO INSTALL AND USE

- Hinged LED gear tray for swift and easy installation
- BESA box fixing points for easy cable entry
- Wall or ceiling mountable
- Exterior or interior use

TYPICAL APPLICATIONS

Its strength and robustness makes the Mini-Max perfect applications such as:

- Housing associations
- Youth centres
- Sports areas
- Walkways
- Car Parks
- Loading bays






For more Information call +44 (0)1420 470 400 email lighting@fernhoward.com or visit www.fernhoward.com

MINI-MAX LED



TECHNICAL INFORMATION



Dimensions:

246 x 246 x 89mm

Weight:

1.3kg

Mounting type:



Wall



Ceiling



Interior



Exterior

Base Colour Options:



White base

RAL 9003



Black base

RAL 9005 50% gloss

Diffuser Options:




Clear Diffuser




Opal Diffuser

LIGHT DISTRIBUTION



cd/klm
— C0 / C180

Clear Diffuser



cd/klm
— C0 / C180

Opal Diffuser

STANDARDS

IP65

IK10


LED

Hinged
gear
tray

EN
60598

RoHS

CE UK
CA



Photometric files at www.fernhoward.com

For more Information call +44 (0)1420 470 400 email lighting@fernhoward.com or visit www.fernhoward.com

MINI-MAX LED

ORDERING GUIDE

Standard Product Code			Light Management Options Suffix*								Performance Data		
	Base Colour	Diffuser Option	DALI	Dimming	Corridor Function	3hr Emergency	Self-Test	DALI Emergency	Microwave Sensor	Photocell	Lumen Output lm	Wattage W	Efficacy lm/W
Mini-Max LED													
FHBL565-160	B/W	CL	DA	DIM	CF	EM	AT	DAEM	MS	PH	1800	13	139
	B/W	OP	DA	DIM	CF	EM	AT	DAEM	MS	PH	1300	13	100
FHBL565-210	B/W	CL	DA	DIM	CF	EM	AT	DAEM	MS	PH	2500	19	132
	B/W	OP	DA	DIM	CF	EM	AT	DAEM	MS	PH	1900	19	100

FHBL565-160

-

B

-

CL

-

EM

Example Code: Mini-Max 13W, Black, Clear with Emergency

*Most combinations are possible except the following:

- DA & DIM – Dimming and DALI cannot be combined
- AT & EM – AT represents Self-Test Emergency configuration
- DA = DALI on Mains Driver only, DAEM = DALI on Emergency Driver only
DA and DAEM can be combined

Lumen Output in EM:

Clear diffuser - 220lm

Opal diffuser - 150lm

50,000
Hours
L70

>80
CRI (Ra)

4000K
Colour
Temperature



Luminaires are manufactured and tested in accordance with BS EN60598.
Incorporated control gear and components comply with BS/VDE standards.
Luminaires are tested in accordance with IES LM-79-08.

Fern-Howard Ltd, 1 Featherstone Rd, Wolverton Mill, Wolverton, Milton Keynes MK12 5TH. Call +44 (0)1420 470 400 or email lighting@fernhoward.com

Registered in England Reg. No. 3202749. We reserve the right to alter specifications without notice in accordance with our policy of continuous product improvement. Design and copyright reserved and our standard Term & Conditions apply. Full details of our warranty can be found on our website.

FernHoward
a Matrix Company