

Rex Slim



Description

Designed for a wide range of applications from domestic to commercial – such as garages, car parks, construction sites and warehouses.

Available in wide range of light output.

Features

- Less weight means easier to install and smaller fixings
- Energy saving highly efficient LED's
- Made from aluminum and toughened glass
- Driverless technology
- 10W-300W options available
- Heavy duty swivel mounting bracket allows the fittings to be installed in a range of positions
- 3-year Guarantee

Range

N6310	10W Rex Slim Floodlight
N6320	20W Rex Slim Floodlight
N6330	30W Rex Slim Floodlight
N6340	50W Rex Slim Floodlight
N6045	70W Rex Slim Floodlight
N6055	100W Rex Slim Floodlight
N6065	150W Rex Slim Floodlight
N6075	200W Rex Slim Floodlight
N6085	300W Rex Slim Floodlight

Available in Black

Technical Specification

Voltage	220V-240V	
Frequency	50-60Hz	
Power Factor	≤0.9	
Colour Temperature	4000K Cool White	
Beam Angle	115°	
Construction	Aluminium Body & Toughened Glass	
IP Rating	IP65	
IK Rating	10W-50W IK07	
	70W-300W IK08	
	10W-50W	0.5m
Cable length	70W-300W	1.5m
	Dimmable	No
Light Source	Non-replaceable LED	
Lifespan	30,000hrs	
Luminous Efficacy	90 lm/W	
Standards	BS EN 60598-1	

No user serviceable parts

Dimensions

	Length	Width	Height
N6310	104mm	27mm	92mm
N6320	125mm	28mm	113mm
N6330	168mm	27mm	162mm
N6340	200mm	36mm	189mm
N6045	281mm	38mm	280mm
N6055	281mm	38mm	280mm
N6065	333mm	51mm	352mm
N6075	350mm	60mm	370mm
N6085	428mm	70mm	416mm

Luminous Flux

N6310	10W	900lm
N6320	20W	1800lm
N6330	30W	2700lm
N6340	50W	4500lm
N6045	70W	6300lm
N6055	100W	9000lm
N6065	150W	13500lm
N6075	200W	18000lm
N6085	300W	27000lm