

Technical Specification

Product Code: MD018SC-DW

Description: 13A/10AX Ingot Double Pole Switch Module



General Information

| | | |
|---------------------------------|------------------------------|--------------------------------|
| Dimensions (mm) | 25 (W) x 53 (H) x 20 (D) | |
| Finish | Satin Chrome | |
| Materials | Rocker Switch: | Urea |
| | Switch Cover: | Stainless Steel |
| | Terminal Screws: | Steel & Yellow Passivated |
| | Internal Busbars: | Formed Pressed Brass |
| Rated Voltage (V~) (Ue) | 250 | Frequency (Hz) 50 |
| Resistive Load Rating (A) | 13 | |
| Inductive Load Rating (AX) | 10 | |
| Load Rating Comments | Suitable For Inductive Loads | |
| Termination Type | Screw | |
| Terminal Size (mm) | Ø3.5 | Terminal Torque Value (Nm) 0.5 |
| Terminal Capacity - Solid (mm²) | 4 x 1.5 or 2 x 2.5 | |
| Modular Rocker Switches | Yes | |
| Double Pole Switch | Yes | |
| Product Marking | Dishwasher | |
| Minimum Back Box Depth (mm) | 16 (25 Flat Plate) | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 10 | |

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

