

**Product Code:** CL675

**Description:** 13A 1 Gang Double Pole Key Lockable Switched Socket With Neon (Double Plate)



### General Information

|                                        |                                                                                                                                                              |                                                                                                                    |
|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| Dimensions (mm)                        | 140 (W) x 80 (H) x 42 (D)                                                                                                                                    |                                                                                                                    |
| Plate Fixing Centres - Horizontal (mm) | 120.6                                                                                                                                                        |                                                                                                                    |
| Style                                  | Metal Clad                                                                                                                                                   |                                                                                                                    |
| Finish                                 | Metal Clad Grey                                                                                                                                              |                                                                                                                    |
| Materials                              | Front Plate & Mounting Box: Electrophoretically Coated Steel<br>Earth Plate & Yoke: Mild Steel<br>Terminals: Brass<br>Internal Busbars: Formed Pressed Brass | Insert: Urea<br>Neon Lens: Polycarbonate<br>Terminal Screws: Steel & Yellow Passivated<br>GridPro Module: GM2018PW |
| Rated Voltage (V~) (Ue)                | 250                                                                                                                                                          | Frequency (Hz) 50                                                                                                  |
| Resistive Load Rating (A)              | 13                                                                                                                                                           |                                                                                                                    |
| Termination Type                       | Screw                                                                                                                                                        |                                                                                                                    |
| Terminal Size (mm)                     | Ø5                                                                                                                                                           | Terminal Torque Value (Nm) 1.2                                                                                     |
| Terminal Capacity - Solid (mm²)        | 3 x 2.5 or 2 x 4                                                                                                                                             |                                                                                                                    |
| Modular Rocker Switches                | Yes                                                                                                                                                          |                                                                                                                    |
| Double Pole Switch                     | Yes                                                                                                                                                          |                                                                                                                    |
| Twin Earth Terminals                   | Yes                                                                                                                                                          |                                                                                                                    |
| Neon Indicator                         | Yes                                                                                                                                                          | Indicator Colour Red                                                                                               |
| Product Marking                        | On & Off                                                                                                                                                     |                                                                                                                    |
| Supplied Back Box Depth (mm)           | 40                                                                                                                                                           |                                                                                                                    |
| Back Box Knockouts - Total (mm)        | 7 x Ø20                                                                                                                                                      |                                                                                                                    |
| Back Box Knockouts - Top (mm)          | 3 x Ø20                                                                                                                                                      | Back Box Knockouts - Sides (mm) 1 x Ø20                                                                            |
| Back Box Knockouts - Bottom (mm)       | 2 x Ø20                                                                                                                                                      | Back Box Knockouts - Rear (mm) None                                                                                |
| Back Box Earth Terminal Supplied       | Yes                                                                                                                                                          |                                                                                                                    |
| Operational Temperature (°C)           | -5 to +40                                                                                                                                                    |                                                                                                                    |
| Warranty (Years)                       | 10                                                                                                                                                           |                                                                                                                    |
| Standards                              | BS EN 60669-1<br>BS 1363-2                                                                                                                                   |                                                                                                                    |

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
Two keys provided (Spare keys available: SP660)  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.