



Lockable switch (with compatible kit)

B

B curve

RCBO's Type A Single Pole B Curve

CU1RCBO6B	6A 30mA B Curve True 6kA RCBO
CU1RCBO10B	10A 30mA B Curve True 6kA RCBO
CU1RCBO16B	16A 30mA B Curve True 6kA RCBO
CU1RCBO20B	20A 30mA B Curve True 6kA RCBO
CU1RCBO32B	32A 30mA B Curve True 6kA RCBO
CU1RCBO40B	40A 30mA B Curve True 6kA RCBO

C

C curve

RCBO's Type A Single Pole C Curve

CU1RCBO6C	6A 30mA C Curve True 6kA RCBO
CU1RCBO10C	10A 30mA C Curve True 6kA RCBO
CU1RCBO16C	16A 30mA C Curve True 6kA RCBO
CU1RCBO20C	20A 30mA C Curve True 6kA RCBO
CU1RCBO32C	32A 30mA C Curve True 6kA RCBO
CU1RCBO40C	40A 30mA C Curve True 6kA RCBO

A

Type A

30mA

Trip Current

○

Large Terminal
Capacity

6kA

True 6kA

—/—

Single Pole
+ Neutral

Warranty (Years): 3
Standards: BS EN 61009-1
Neutral Flylead (mm): 450
Dimensions (mm): 17.8 (W) x 91.8 (H) x 76.6 (D)



Lockable switch (with compatible kit)

B

B curve

RCBO's Type A 2 Module Double Pole B Curve

CU2RCBO45B	45A 30mA B Curve True 6kA RCBO
CU2RCBO50B	50A 30mA B Curve True 6kA RCBO
CU2RCBO63B	63A 30mA B Curve True 6kA RCBO

C

C curve

RCBO's Type A 2 Module Double Pole C Curve

CU2RCBO45C	45A 30mA C Curve True 6kA RCBO
CU2RCBO50C	50A 30mA C Curve True 6kA RCBO
CU2RCBO63C	63A 30mA C Curve True 6kA RCBO

A

Type A

30mA

Trip Current

○

Large Terminal
Capacity

6kA

True 6kA

—/—

Single Pole
+ Neutral

Warranty (Years): 3
Standards: BS EN 61009-1
Dimensions (mm): 35.6 (W) x 84 (H) x 76.6 (D)