

Ei1000G

SmartLINK Gateway



- Enables remote data management of alarm systems via the SmartLINK Cloud Portal
- Transmits data over GSM network
- Unique House Coding feature
- Easy setup and configuration using dedicated SmartLINK App
- Compatible with SmartLINK & RadioLINK+ Alarms and Accessories



Description

The SmartLINK Gateway allows remote monitoring of SmartLINK and RadioLINK+ alarm systems via the SmartLINK Portal. It receives information from the alarms and reports events up to the portal via its GSM connection. For use with the SmartLINK App

Technical

RF Frequency (MHz)	868	RF Range (m)	>100 in free air
Indicators	Green - Power / Blue - RF communication / Yellow - GSM communication	Supply Voltage (V)	230
Voltage Type	AC	Battery Type	NiMH rechargeable
Power Consumption (W)	1.5	Technologies	SmartLINK

Dimensions & Weights

Depth (mm)	81	Height (mm)	123
Width (mm)	175	Product weight (kg)	0.45
Packaged weight (kg)	0.572		

Approvals & Warranty

Certification/Approvals	Internet of Things (IoT)	Warranty	5 year warranty
EAN Number	5099383007060		

Environmental

Humidity Range (%)	15-95	Temperature Range (°C)	-10 to 40
---------------------------	-------	-------------------------------	-----------