

Ei660iRF



RadioLINK+ Multi-Sensor Fire Alarm



- Contains both an Optical and Heat sensor for a total fire response
- 10 year Lithium battery powered
- Built in AudioLINK+ data extraction technology
- Kitemarked to BS EN14604:2005 & BS5446-2:2003
- RadioLINK+ Wireless interconnection
- 5 year guarantee



Description

The Ei660iRF is a battery powered Multi-Sensor Fire Alarm that contains a sealed in, tamper proof lithium battery that will last for the full 10 year life of the alarm. It is able to wirelessly interconnect with any other RadioLINK, RadioLINK+ and SmartLINK products and contains built-in AudioLINK+ data extraction technology. It also features a large test button and twist on base with an anti-tamper locking option

Technical

Sensor Type	Optical and Heat - with dust compensation	RF Frequency (MHz)	868.499
RF Range (m)	>100 in free air	Indicators	Red - Fault / Blue - RF transmission / Green - Monitoring
Battery Type	Lithium primary	Technologies	AudioLINK+ / RadioLINK+

Dimensions & Weights

Depth (mm)	120	Height (mm)	58
Width (mm)	120	Product weight (kg)	0.224
Packaged weight (kg)	0.259		

Approvals & Warranty

Certification/Approvals	EN 14604: 2005, BS 5446-2:2003	Warranty	5 year warranty
EAN Number	5099383010367		

Environmental

Humidity Range (%)	15-95	Temperature Range (°C)	-10 to 40
---------------------------	-------	-------------------------------	-----------