

BCAB-L CP 23-25 COMBI 607 BK



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Type	BCAB-L CP 23-25 COMBI 607 BK
WISKA-Order no.	10110317

Description:

BC-KIT 3 Includes:

10 x EBFS 23-25/ 2 x COMBI 607/ 10m BCAB-L 23/ 10 x EMUG 20

Technical description of components:

EBFS 23-25 - Material number 10106869

Material Conduit fitting polyamide UL94-V0

Material Connection thread polyamide UL94-V0

Material sealing gasket TPU

Protection class IP66, IP68

Temp. range min -40 °C

Temp. range max 100 °C

Operational areas EN 45545 - Railway

NW 23

Thread type M

Ø Connection thread D 25

Lead 1,5

Length screw-in thread L 14 mm

Ø closure VD 42 mm

Ø inside 19 mm

Key width SW 36 mm

Total length TL 50,3 mm

Type of conduit fitting straight

UL 1696 Yes

Product Color RAL 9005

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk

COMBI 607 - Material number 10060648

Material Polypropylene

Material sealing gasket TPE

Temp. range min -30 °C

Temp. range max 100 °C

Temperatures during install. -5 °C - 60 °C

Protection class IP66 / IP67

Glow wire test 750 °C

Voltage 690 V

Rated cross section 6 mm²

Fixing 4 internal openings

Ø cable diameter min 5,2 mm

Ø cable diameter max 17 mm

External dimensions LxWxH 110 x 110 x 66mm

Product Color RAL 9005

BCAB-L 23 - Material number 10109186

Material PA6 UL94-HB

Temp. range min -40 °C

Temp. range max 140 °C

Operational areas Mechanical plant engineering

Product Color RAL 9005

NW 23

External diameter ED 28,3 mm

Ø inside 23,4 mm

Profile width A 3,4 mm

Width B 2,3 mm

Bending radius R 60 mm

Wall thickness S 0,3 mm

Model light

EMUG 20 - Material number 10061782

Material Polyamide, fibre reinforced

Temp. range min -40 °C

Temp. range max 100 °C

Glow wire test 650 °C

Thread type M

Ø Connection thread D 20

Lead 1,5

Key width SW 27 mm

Collar diameter (E) 29 mm

Total length TL 5 mm

Product Color RAL 9005

15.03.2023

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk