

Product datasheet

Specifications



PowerPacT 4 - panelboard - 1600A - 42 ways - 1P - Style G - top cable entry

MG16C14T

Main

Range	PowerPact
Product or component type	Panelboard
Product name	PowerPacT 4
Device application	Distribution
Provided equipment	removable bottom gland plate end cover

Complementary

[In] rated current	1600 A
Number of ways	42 (1P) 14 ways (3P)
[Ue] rated operational voltage	415 V 50 Hz AC
Breaking capacity	50 kA AC 1 s
Enclosure material	epoxy-polyester powder steel
Cable entry	Top at main
Device mounting	Floor mounted

Environment

IP degree of protection	IP3x
Standards	BS EN 60439-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)