


EZ-Path® fire rated pathway Series 44+

selection chart

CE marked certification

Fire resistance : EN 1366-3 Classification : EN 13501-2
ETA 18 / 0412

All EZ-Path systems are approved empty up to 100 % visual fill of cable



CM250058 (EZD44T)

Cat. Nos.		Plate kit	Plate dim. (mm) (w x h)	EZ-Path systems		Opening dim. (mm) (w x h or Ø)	Ø cables (mm)
1 x CM250058 (1 x EZD44T) (grouted with mortar)	1 x	—	—	=		Ø 152 - Ø 155 or width = 138 (+/- 16 mm) height = 143 (+/- 12 mm) max. 154 x 155	OD ≤ Ø 21
2 x CM250058 (2 x EZD44T) (grouted with mortar)	2 x	—	—	=		width = 240 (+/- 16 mm) height = 143 (+/- 12 mm) max. 256 x 155	OD ≤ Ø 21
3 x CM250058 (3 x EZD44T) (grouted with mortar)	3 x	—	—	=		width = 342 (+/- 16 mm) height = 143 (+/- 12 mm) max. 358 x 155	
4 x CM250058 (4 x EZD44T) (grouted with mortar)	4 x	—	—	=		width = 444 (+/- 16 mm) height = 143 (+/- 12 mm) max. 460 x 155	
5 x CM250058 (5 x EZD44T) (grouted with mortar)	5 x	—	—	=		width = 546 (+/- 16 mm) height = 143 (+/- 12 mm) max. 562 x 155	
1 x CM250058 + CM350700 (1 x EZD44T + EZP144WE)	1 x		178 x 191	=		Ø 152 - Ø 155 or 105 x 118	OD ≤ Ø 21
1 x CM250058 + CM350701 (1 x EZD44T + EZP144RSE)	1 x		178 x 191	=		Ø 152 - Ø 155 or 105 x 118	OD ≤ Ø 21
1 x CM250058 + CM250230 (1 x EZD44T + EZP144WT)	1 x		178 x 237	=		Ø 152 - Ø 155 or 105 x 118	OD ≤ Ø 80
1 x CM250058 + CM350702 (1 x EZD44T + EZP544WE)	1 x		610 x 196	=		105 x 118	OD ≤ Ø 21
2 x CM250058 + CM350702 (2 x EZD44T + EZP544WE)	2 x			=		206 x 118	
3 x CM250058 + CM350702 (3 x EZD44T + EZP544WE)	3 x			=		309 x 118	
4 x CM250058 + CM350702 (4 x EZD44T + EZP544WE)	4 x			=		412 x 118	
5 x CM250058 + CM350702 (5 x EZD44T + EZP544WE)	5 x			=		515 x 118	
1 up to 5 x CM250058 + CM350702 (1 up to 5 x EZD44T + EZP544WE) Rockwool FirePro® Ablative Coated Batt	1 up to 5 x		610 x 196	=		Max. 568 x 800	OD ≤ Ø 21

Accessories for Series 44+

Extension	CM250178 (EZD44ES)		Length 152 mm for use with CM250058 (EZD44T)
Dropout	CM250306 (RCM44)		For use with CM250058 (EZD44T)