


Product data sheet

Specifications



Function module, TeSys Ultra, 1NO +1NC, 24 to 240VAC/DC, Front side, thermal overload signalling

LUFDH11

Main

Range	TeSys
Device short name	LUF
Product or component type	Function module
Product compatibility	LUCC LUCB LUCD

Complementary

Mounting mode	Plug-in
Mounting location	Front side
Main function available	Thermal overload signalling and manual reset
Auxiliary contact composition	1 NO + 1 NC
Communication of faults	LED front panel
[Us] rated supply voltage	24...240 V DC 24...240 V AC
Current consumption	7 mA at 24 V DC 1.1 mA at 240 V AC
Discrete output function	1 NO + 1 NC (AC-15) at 230 V - power: 400 VA - electrical service life: 100000 cycles 1 NO + 1 NC (DC-13) at 24 V - power: 50 W - electrical service life: 100000 cycles
[Ith] conventional free air thermal current	2 A 70 °C
Short-circuit protection	2 A fuse gG conforming to IEC 60947-5-1
Input type	Remote reset - cable cross section: 0.2...1.5 mm² <500 m - relative impedance: 50 Ohm 52.8 mH - cable capacitance: 0.093 nF
Connection pitch	5.08 mm
Connections - terminals	Screw clamp terminals 2 cable(s) 0.2...1 mm² rigid without cable end Screw clamp terminals 2 cable(s) 0.25...1 mm² flexible with cable end Screw clamp terminals 2 cable(s) 0.5...1 mm² flexible with cable end
Tightening torque	0.5...0.6 N.m - with screwdriver 3.5 mm flat
Net weight	0.06 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	3.3 cm
Package 1 Width	4.7 cm
Package 1 Length	10.5 cm
Package 1 Weight	75.0 g
Unit Type of Package 2	S01
Number of Units in Package 2	15
Package 2 Height	15.0 cm
Package 2 Width	15.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	1.346 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)