

Eaton 239101

Catalog Number: 239101

Eaton Moeller series xEffect - FAZ6 MCB. Miniature circuit breaker (MCB), 10 A, 2p, characteristic: C, 6 kA

General specifications

Product Name	Catalog Number
Eaton Moeller series xEffect - FAZ6 MCB 239101	
Model Code	EAN
FAZ6-C10/2	4015082391010
Product Length/Depth	Product Height
85 mm	73 mm
Product Width	Product Weight
35.4 mm	.216 kg
Compliances	Model Code
RoHS conform	FAZ6-C10/2

Delivery programme

Number of poles (total)

2

Number of poles (protected)

2

Release characteristic

C

Amperage Rating

10 A

Technical data - electrical

Voltage type

AC

Rated operational voltage (U_e) - max

230 V

Rated insulation voltage (U_i)

440 V

Rated impulse withstand voltage (U_{imp})

4 kV

Frequency rating - min

50 Hz

Frequency rating - max

60 Hz

Rated short-circuit breaking capacity (EN 60898) at 230 V

6 kA

Rated short-circuit breaking capacity (EN 60898) at 400 V

6 kA

Rated short-circuit breaking capacity (IEC 60947-2) at 230 V

10 kA

Rated short-circuit breaking capacity (IEC 60947-2) at 400 V

10 kA

Overvoltage category

III

Pollution degree

2

Technical data - mechanical

Width in number of modular spacings

2

Built-in depth

70.5 mm

Degree of protection

IP20

Connectable conductor cross section (solid-core) - min

1 mm²

Design verification as per IEC/EN 61439 - technical data

Rated operational current for specified heat dissipation (I_n)

10 A

Equipment heat dissipation, current-dependent

3 W

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

75 °C

Connectable conductor cross section (solid-core) - max
25 mm²

Connectable conductor cross section (multi-wired) - min
1 mm²

Connectable conductor cross section (multi-wired) - max
25 mm²

Design verification as per IEC/EN 61439

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Additional information

Current limiting class

3

Features

Additional equipment possible

Resources

Application notes

[eaton-maximum-cable-lengths-for-eatons-protective-devices-brochure-br034006en-en-us.pdf](#)

Catalogues

[eaton-xeffect-faz-mcb-catalog-ca003028en-en-us.pdf](#)

[eaton-xeffect-industrial-switchgear-range-catalog-ca003002en-en-us.pdf](#)

Certification reports

[DA-DC-03_FAZ6](#)

Drawings

[Mas_FAZ_2](#)

[eaton-xeffect-faz-mcb-dimensions-002.jpg](#)

[FAZ6_i2t_c_IEC947](#)

[eaton-xeffect-faz6-mcb-3d-drawing-002.jpg](#)

[FAZ6_idl_c_IEC947](#)

[eaton-xeffect-faz6-mcb-3d-drawing-005.jpg](#)

Installation instructions

[IL019140ZU](#)

Wiring diagrams

[eaton-xpole-mmc4-6-m-mcb-wiring-diagram-003.jpg](#)

[PLS_2P](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)