

Product datasheet

Specifications



Molded case circuit breaker,
PowerPacT 4, 4P, Icu 36kA, TMD
thermal magnetic trip unit, 63A
rating

PP40634X

EAN Code : 5018934030654

Main

Range of product	PowerPacT 4
Product or component type	Circuit breaker
Device application	Distribution
Poles description	4P
[In] rated current	63 A at 40 °C
[Ue] rated operational voltage	415 V AC 50/60 Hz
Suitability for isolation	Yes conforming to BS EN 60947-2
Utilisation category	Category A
[Icu] rated ultimate short-circuit breaking capacity	36 kA Icu at 415 V AC 50/60 Hz
Performance level	F
Trip unit name	TM-D
Trip unit technology	Thermal-magnetic
Trip unit protection functions	LI
Control type	Toggle
Circuit breaker mounting mode	Panel-mounted

Complementary

[Ui] rated insulation voltage	800 V
[Uimp] rated impulse withstand voltage	8 kV
[Ics] rated service short-circuit breaking capacity	36 kA at 415 V AC 50/60 Hz
Mechanical durability	50000 cycles
Electrical durability	50000 cycles at 440 V In/2 30000 cycles at 440 V In
Power dissipation per pole	8.61 W
Mounting support	Backplate
Mounting position	Horizontal and vertical
Number of modules	4 module(s)35 mm
Protection type	L : for overload protection (thermal)

	I : for short-circuit protection (magnetic)
Trip unit rating	63 A at 40 °C
Long-time pick-up adjustment type Ir (thermal protection)	Fixed
[Ir] long-time protection pick-up adjustment range	0.7...1 x In
Long-time protection delay adjustment type tr	Fixed
Neutral protection settings	1 x Ir
Instantaneous protection pick-up adjustment type li	Fixed
[li] instantaneous protection pick-up adjustment range	500 A
Earth-leakage protection	Without
Contact position indicator	Yes
Width	140 mm
Depth	86 mm
Height	161 mm
Net weight	2.4 kg
Product destination	250 A panelboard 400/630 A panelboard
Colour	Grey

Environment

Standards	BS EN 60947-2
Electrical shock protection class	Class II
Pollution degree	3 conforming to EN/IEC 60664-1
IP degree of protection	IP40 conforming to EN/IEC 60529
IK degree of protection	IK07 conforming to EN/IEC 62262
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C
Operating altitude	0...2000 m without derating 2000...5000 m with derating

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15 cm
Package 1 Width	25.5 cm
Package 1 Length	37.5 cm
Package 1 Weight	4.72 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	60
Package 2 Height	112 cm
Package 2 Width	100 cm

Package 2 Length	120 cm
Package 2 Weight	293.2 kg
Contractual warranty	
Warranty	18 months

Recommended replacement(s)