

PRODUCT DATASHEET SMART+ WIFI SPOT R63 60 4.7W Multicolor E27

SMART+ SPOT CONCENTRA Multicolor | SMART+ SPOT CONCENTRA LAMPS WITH WIFI TECHNOLOGY



Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Wireless control via app
- Easy to install and use
- Contains no mercury

Product features

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 9.0)
- Controllable via Google Assistant and Amazon Alexa possible
- Adjustable light color via Tunable White: Warm White to Cool White (2,700 K...6,500 K)
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Network protocol: WiFi
- Lifetime: up to 15,000 h




TECHNICAL DATA

Electrical data

Nominal wattage	4.7 W
Construction wattage	4.70 W
Nominal voltage	220 V
Nominal current	40 mA
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor λ	> 0.50
Claimed equiv. conventional lamp power	60 W

Photometrical data

Light color (designation)	RGBW
Lumen main.fact.at end of nom.life time	0.70
Standard deviation of color matching	≤6 sdcm
Nominal luminous flux	345 lm
Luminous flux	345 lm
Luminous efficacy	73 lm/W
Luminous intensity	380 cd
Adjustable color temperature	27006500 K
Color temperature	27006500 K
Color rendering index Ra	80
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.9



Light technical data

Beam angle	45 °
Starting time	< 0.5 s

Warm-up time (60 %)	< 0.50 s

Dimensions & Weight

Product weight	84.00 g
Diameter	63.00 mm
Maximum diameter	102 mm
Length	102.00 mm
Width	63.00 mm
Height	63.00 mm
Outer bulb [PICOS]	R63

Lifespan

Number of switching cycles	100000
Lifespan	20000 h
Lumen maintenance at end of serv	0.70

Temperatures & operating conditions

Ambient temperature range −20+40 °C	Ambient temperature range	-20+40 °C
-------------------------------------	---------------------------	-----------

Additional product data

Base (standard designation)	E27
-----------------------------	-----

Capabilities

Dimmable	Yes
Compatible smart home technology	Google Assistant / Amazon Alexa

Certificates & Standards

Energy efficiency class	F ¹⁾
Energy consumption	5.00 kWh/1000h
Standards	CE

 $^{1) \ {\}sf Energy \ efficiency \ class \ (EEC) \ on \ a \ scale \ of \ A \ (highest \ efficiency) \ to \ G \ (lowest \ efficiency)}$

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	DLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	yes
Color-tuneable light source	yes
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	RANGE
Standby power	0.50
Networked standby power for CLS	0.50
Claim of equivalent power	Yes
Chromaticity coordinate x	0.463
Chromaticity coordinate y	0.420
R9 Colour rendering index	0.00
Beam angle correspondence	NARROW_CONE_90
Survival factor	0,90
Displacement factor	0.50
LED light source replaces a fluorescent light source	No
EPREL ID	528231
Model number	AC33944

DOWNLOAD DATA

	DOWNLOAD DATA
POF	Declarations Of Conformity CE
PDF	Installation guide

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075609570	Folding box 1	66 mm x 96 mm x 154 mm	169.00 g	0.98 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075609587	Shipping box 4	210 mm x 165 mm x 145 mm	790.00 g	5.02 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.