

Cat No.									Description	Inner Carton	Outer Carton
---------	--	--	--	--	--	--	--	--	-------------	--------------	--------------

10 Amp 10AX Plate Switches

Brushed Steel	Polished Chrome	Black Nickel	Antique Brass	Brushed Iridium	Cream	Gloss White	Matt Black	Pearl Nickel			
NBS12	NPC12	NBN12	NAB12	NBI12	NCR12	NPW12	NMB12	NPR12	1 gang, 2 way	5	50
NBS13	NPC13	NBN13	NAB13	NBI13	NCR13	NPW13	NMB13	NPR13	intermediate	5	50
NBS14	NPC14	NBN14	-	-	-	-	-	-	bell push **	5	50
NBS15	NPC15	NBN15	-	-	-	-	-	-	3 pole fan isolator	5	50
NBS42	NPC42	NBN42	NAB42	NBI42	NCR42	NPW42	NMB42	NPR42	2 gang, 2 way	5	50
NBS43	NPC43	NBN43	NAB43	NBI43	NCR43	NPW43	NMB43	NPR43	3 gang, 2 way	5	50
NBS44	NPC44	NBN44	-	-	-	-	-	-	4 gang, 2 way	5	50

- Plate switches manufactured to BS EN 60669-1, fan isolator to IEC 60669-2-4.

- Terminal capacity 4 x 1.0mm², 4 x 1.5mm², 2 x 2.5mm² & 1 x 4.0mm²

- Captive terminal screws

- Minimum mounting box depth:

1 & 2 gang 16mm

3 & 4 gang 25mm

- **Bell push switch made to order, contact Customer Services for more details



NBS12



NPC42



NAB43

13 Amp Switched Socket Outlets

Brushed Steel	Polished Chrome	Black Nickel	Antique Brass	Brushed Iridium	Cream	Gloss White	Matt Black	Pearl Nickel			
NBS21W	NPC21W	-	-	-	-	-	-	-	1 gang	5	50
NBS21B	-	NBN21B	NAB21B	NBI21B	NCR21B	NPW21B	NMB21B	NPR21B		5	50
NBS21G	-	-	-	-	-	-	-	-			
NBS22W	NPC22W	-	-	-	NCR22W	NPW22W	NMB22W	NPR22W	2 gang	5	50
NBS22B	-	NBN22B	NAB22B	NBI22B	-	-	-	-		5	50
NBS22G	-	-	-	-	-	-	-	-			



NPC21W



NCR22W

- Manufactured to BS 1363 part 2
- Brushed Steel insert colours = White (W), Grey (G) and Black (B)
- Terminal capacity 3 x 2.5mm², 3 x 4.0mm² & 2 x 6.0mm²
- Minimum mounting box depth 25mm
- Twin earth fitted as standard to allow a double earth facility for installations requiring high integrity protective connection Ref. BS 7671:2008

13 Amp Switched Socket with USB Charger

Brushed Steel	Polished Chrome	Black Nickel	Antique Brass	Brushed Iridium	Cream	Gloss White	Matt Black	Pearl Nickel			
NBS22UW	NPC22UW	-	-	-	NCR22UW	NPW22UW	-	NPR22UW	2 gang + 2 USB (2.1A), White Insert	5	50
NBS22UG	-	-	-	-	-	-	-	-	2 gang + 2 USB (2.1A), Grey Insert	5	50
NBS22UB	-	NBN22UB	NAB22UB	NBI22UB	-	-	NMB22UB	-	2 gang + 2 USB (2.1A), Black Insert	5	50



NBS22UG

- Ideal for charging iPad, iPhone, tablets, mobiles, cameras and more
- 2 x Type A USB sockets - 2.1A total output, 5V
- Minimum mounting box depth 25mm - ideal for retrofit.
- Twin earth fitted as standard
- Terminal capacity 3 x 2.5mm², 3 x 4.0mm² & 2 x 6.0mm²
- 10 year guarantee

