

Switch-Interlocked **RCD** Protected Sockets

Switched and interlocked units incorporate a mechanical interlock mechanism which prevents the switch from being turned 'ON' until the plug is fully inserted. The plug cannot be withdrawn until the switch is turned to the 'OFF' position.

The switch can be padlocked in the 'OFF' position. Units are supplied with RCD (for earth fault protection) with sensitivity of 30MA/30MS as standard (others available upon request). ALL UNITS ARE INTERNALLY **PRE-WIRED**.

16A Socket = 25A RCD

32A Socket = 40A RCD

63A Socket = 63A RCD

Sockets available at IP44 Splashproof or IP67 Watertight



One Switched Interlocked Socket IP44 Protected by 1x 30MA RCD			
16A	240	2P+E	880448
32A	240	2P+E	880450
63A	240	2P+E	880452

One Switched Interlocked Socket IP67 Protected by 1x 30MA RCD			
16A	240	2P+E	880118
32A	240	2P+E	880122
63A	240	2P+E	880126



One Switched Interlocked Socket IP44 Protected by 1x 30MA RCD			
16A	110	2P+E	880466
32A	110	2P+E	880468
63A	110	2P+E	880470

One Switched Interlocked Socket IP67 Protected by 1x 30MA RCD			
16A	110	2P+E	880418
32A	110	2P+E	880422
63A	110	2P+E	880426



One Switched Interlocked Socket IP44 Protected by 1x 30MA RCD			
16A	415	3P+E	880454
32A	415	3P+E	880456
63A	415	3P+E	880458

One Switched Interlocked Socket IP67 Protected by 1x 30MA RCD			
16A	415	3P+E	880130
32A	415	3P+E	880134
63A	415	3P+E	880138



One Switched Interlocked Socket IP44 Protected by 1x 30MA RCD			
16A	415	3P+N+E	880460
32A	415	3P+N+E	880462
63A	415	3P+N+E	880464

One Switched Interlocked Socket IP67 Protected by 1x 30MA RCD			
16A	415	3P+N+E	880142
32A	415	3P+N+E	880146
63A	415	3P+N+E	880150

Illustrations show IP67

	16			32			63		
	3	4	5	3	4	5	3	4	5
Amperes									
Poles									
a	134	134	134	134	134	134	180	180	180
b	365	365	365	365	365	365	460	460	460
c	117	117	117	117	117	117	160	160	160
d	348	348	348	348	348	348	440	440	440
e	136	136	143	152	152	158	191	191	191
f	389	389	389	399	399	399	500	500	500
g	6.5	6.5	6.5	6.5	6.5	6.5	8	8	8
h	8	8	8	8	8	8	6.5	6.5	6.5
Cable Entry	M25	M25	M25	M25	M25	M25	M32	M32	M32

One top and two bottom cable entries in size indicated above

Units rated at 125A also available