

Switch-Interlocked Combination Units

CEE NORM

Switch-Interlocked RCD Protected Sockets

Switched and interlocked units incorporate a mechanical interlock mechanism which prevents the switch from being turned 'ON' until the plug is fully inserted. The plug cannot be withdrawn until the switch is turned to the 'OFF' position.

The switch can be padlocked in the 'OFF' position. Units are supplied with RCD (for earth fault protection) with sensitivity of 30MA/30MS as standard (others available upon request). ALL UNITS ARE INTERNALLY **PRE-WIRED**.

16A Socket = 25A RCD

32A Socket = 40A RCD

63A Socket = 63A RCD

Sockets available at IP44 Splashproof or IP67 Watertight



One Switched Interlocked Socket
IP44 Protected by 1x 30MA RCD

16A	240	2P+E	880448
32A	240	2P+E	880450
63A	240	2P+E	880452

One Switched Interlocked Socket
IP67 Protected by 1x 30MA RCD

16A	240	2P+E	880118
32A	240	2P+E	880122
63A	240	2P+E	880126



One Switched Interlocked Socket
IP44 Protected by 1x 30MA RCD

16A	110	2P+E	880466
32A	110	2P+E	880468
63A	110	2P+E	880470

One Switched Interlocked Socket
IP67 Protected by 1x 30MA RCD

16A	110	2P+E	880418
32A	110	2P+E	880422
63A	110	2P+E	880426



One Switched Interlocked Socket
IP44 Protected by 1x 30MA RCD

16A	415	3P+E	880454
32A	415	3P+E	880456
63A	415	3P+E	880458

One Switched Interlocked Socket
IP44 Protected by 1x 30MA RCD

16A	415	3P+E	880130
32A	415	3P+E	880134
63A	415	3P+E	880138



One Switched Interlocked Socket
IP44 Protected by 1x 30MA RCD

16A	415	3P+N+E	880460
32A	415	3P+N+E	880462
63A	415	3P+N+E	880464

One Switched Interlocked Socket
IP67 Protected by 1x 30MA RCD

16A	415	3P+N+E	880142
32A	415	3P+N+E	880146
63A	415	3P+N+E	880150

Illustrations show IP67

	16			32			63		
	3	4	5	3	4	5	3	4	5
a	134	134	134	134	134	134	180	180	180
b	365	365	365	365	365	365	460	460	460
c	117	117	117	117	117	117	160	160	160
d	348	348	348	348	348	348	440	440	440
e	136	136	143	152	152	158	191	191	191
f	389	389	389	399	399	399	500	500	500
g	6.5	6.5	6.5	6.5	6.5	6.5	8	8	8
h	8	8	8	8	8	8	6.5	6.5	6.5
Cable Entry	M25	M25	M25	M25	M25	M25	M32	M32	M32

One top and two bottom cable entries in size indicated above

Units rated at 125A also available

Switch-Interlocked Combination Units

CEE NORM

Switch-Interlocked Sockets Protected by Both RCD & MCB

These units are supplied with both RCD (earth fault protection) and MCB (overcurrent protection). Units are supplied with "C" type MCB's as standard. ALL UNITS ARE INTERNALLY **PRE-WIRED**.

Socket Rating

16 Amps
32 Amps
63 Amps

RCD Rating & Tripping

25 Amps 30MA
40 Amps 30MA
63 Amps 30MA

MCB Rating


16 Amps
32 Amps
63 Amps

Note: 16A & 32A units can be supplied with an **RCBO** (Earth Fault & Overcurrent Protection) in same module. Please ask for details.

Sockets available at IP44 Splashproof or IP67 Watertight

 3 Poles 240V 2P+E	One Switched Interlocked Socket IP44 Protected by 1x 30MA RCD & 1x MCB			
	16A	240	2P+E	880449
	32A	240	2P+E	880451
	63A	240	2P+E	880453
 3 Poles 110V 2P+E	One Switched Interlocked Socket IP44 Protected by 1x 30MA RCD & 1x MCB			
	16A	110	2P+E	880467
	32A	110	2P+E	880469
	63A	110	2P+E	880471
 4 Poles 415V 3P+E	One Switched Interlocked Socket IP67 Protected by 1x 30MA RCD & 1x MCB			
	16A	240	2P+E	880119
	32A	240	2P+E	880123
	63A	240	2P+E	880127
 5 Poles 415V 3P+N+E	One Switched Interlocked Socket IP44 Protected by 1x 30MA RCD & 1x MCB			
	16A	415	3P+E	880455
	32A	415	3P+E	880457
	63A	415	3P+E	880459
 5 Poles 415V 3P+N+E	One Switched Interlocked Socket IP67 Protected by 1x 30MA RCD & 1x MCB			
	16A	415	3P+N+E	880131
	32A	415	3P+N+E	880135
	63A	415	3P+N+E	880139
 5 Poles 415V 3P+N+E	One Switched Interlocked Socket IP44 Protected by 1x 30MA RCD & 1x MCB			
	16A	415	3P+N+E	880461
	32A	415	3P+N+E	880463
	63A	415	3P+N+E	880465
 5 Poles 415V 3P+N+E	One Switched Interlocked Socket IP67 Protected by 1x 30MA RCD & 1x MCB			
	16A	415	3P+N+E	880143
	32A	415	3P+N+E	880147
	63A	415	3P+N+E	880151

Illustrations show IP67

	Amperes	16			32			63		
	Poles	3	4	5	3	4	5	3	4	5
	a	134	134	134	134	134	134	180	180	180
	b	365	365	365	365	365	365	460	460	460
	c	117	117	117	117	117	117	160	160	160
	d	348	348	348	348	348	348	440	440	440
	e	136	136	143	152	152	158	191	191	191
	f	389	389	389	399	399	399	500	500	500
	g	6.5	6.5	6.5	6.5	6.5	6.5	8	8	8
	h	8	8	8	8	8	8	6.5	6.5	6.5
	Cable Entry	M25	M25	M25	M25	M25	M25	M32	M32	M32

One top and two bottom cable entries in size indicated above

Units rated at 125A also available