



Springbok Lite 21,000lm

150W High bay luminaire (Replaces 250W or 4X49W T5)

Features

IK rating	IK08
IP rating	IP65
Sensor Option	Microwave & Daylight
Dimmable Option	No
LED Lifetime	54,000h L70
CRI	80 Ra
SDCM	5 SDCM
Emergency Option	Yes

Installation information

Install Connector Type	Flying lead
Inrush Current	100A 0.42ms
Construction Material	ADC12 aluminium alloy tempered glass
Weight	1.86
Maximum Ambient Temperature	-20°C to +40°C
UK Building Regulations	Part P
Electric Class (1, 2, 3)	1

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	EM
HBL2N	Matt black RAL9017	150W	4000K	110°	21000	140	530
HBL2NEM	Matt black RAL9017	150W	4000K	110°	21000	140	530

Wiring information

Cable / Flying Lead	1.5m H05RN-F 3x1.0mm ² Ø7mm
Type of Wiring Required	Parallel

Accessories

HBLMWS	High Bay Sbok Lite, Microwave sensor kit inc junction box and counterweight	Sold Separately
HBREM	High Bay Sbok Lite, Remote control for commissioning HBLMWS	Sold Separately
HBL2REFR	High Bay Sbok Lite, 150W 80-degree refractor	Sold Separately



collingwood

01604 495 151
collingwoodlighting.com

collingwoodled

/collingwoodlighting

collingwoodlighting

Guarantee

4 years, 2 years on battery, 2 years on-site

Features & benefits

High efficacy of 140lm/W

Very light weight for easy installation

Emergency option available

Economical high bay for fast return on investment

Easy to add microwave sensor kit includes junction box and counter weight

On/off control with time delay and daylight switching (8-15 metres max)

Suitable for jack chain, M10 drop rod or catenary wire suspension

Pre-wired with 1.5m of H05RN-F cable for ease and speed of installation

Replaceable driver for easy maintenance

IK08 for robust impact protection

Beam angle: 110°

