






01604 495 151
collingwoodlighting.com

 collingwoodled
 /collingwoodlighting
 collingwoodlighting

Springbok Lite 11,000lm

80W High bay luminaire (Replaces 150W or 2x80W T5)

Features

IK rating	IK08
IP rating	IP65
Sensor Option	Microwave & Daylight
Dimmable Option	No
LED Lifetime	54,000h L70
CRI	80 Ra
SDCM	5 SDCM
Emergency Option	Yes

Installation information

Install Connector Type	Flying lead
Inrush Current	100A 0.42ms
Construction Material	ADC12 aluminium alloy tempered glass
Weight	1.60
Maximum Ambient Temperature	-20°C to +40°C
UK Building Regulations	Part P
Electric Class (1, 2, 3)	1

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	EM
HBLIN	Matt black RAL9017	80W	4000K	110°	11000	138	530
HBLINEM	Matt black RAL9017	80W	4000K	110°	11000	138	530

Wiring information

Cable / Flying Lead	1.5m H05RN-F 3x1.0mm ² Ø7mm
Type of Wiring Required	Parallel

Accessories

HBLMWS	High Bay Sbok Lite, Microwave sensor kit inc junction box and counterweight	Sold Separately
HBREM	High Bay Sbok Lite, Remote control for commissioning HBLMWS	Sold Separately
HBLIREFR	High Bay Sbok Lite, 80W 80-degree refractor	Sold Separately

Guarantee

4 years, 2 years on battery, 2 years on-site

Features & benefits

High efficacy of 138lm/W
Very light weight for easy installation
Emergency option available
Economical high bay for fast return on investment
Easy to add microwave sensor kit includes junction box and counter weight
On/off control with time delay and daylight switching (8-15 metres max)
Suitable for jack chain, M10 drop rod or catenary wire suspension
Pre-wired with 1.5m of H05RN-F cable for ease and speed of installation
Replaceable driver for easy maintenance
IK08 for robust impact protection

Beam angle: 110°

