



# Salvus Emergency Escape Route

150lm, manual test emergency escape route

## Features

IK rating	IK08
IP rating	IP20
CRI	70 Ra

## Installation information

Install Connector Type	Push-fit connector
Cut Out Size	48mm
Inrush Current	17.6A 92s
Construction Material	Lens PMMA housing PC
Weight	0.2Kg
Maximum Ambient Temperature	45°C
Electric Class (1, 2, 3)	2

## Photometrics @ 25°C

Product code	Feature II	Feature III	W	Colour	Beam	lm	lx @ 1m
EMER120MO35	Open Area Lens	Manual Test	1W	5300K	140°	120	60 @ 70°
EMER120MC35	Corridor Lens	Manual Test	1W	5300K	140°	120	253 @ 74°

## Accessories

No accessories required



collingwood

01604 495 151  
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

## Guarantee

2 Year Extended Warranty

## Features & benefits

Non-maintained, so the light source is off when the mains power is on

Manual test

Lithium batteries are long-lasting and have a long-life

Discrete and elegant design, making it ideal for use within rooms or corridors

Housing is rugged and made from polycarbonate

Supplied with additional lens, for an asymmetric beam angle, ideal to illuminate corridors and delivering 135 lm

## Beam angle:

