



-  LED
-  5 Year Warranty
-  IP65
-  Photocell
-  ✓ IES Files
-  Double Insulated
-  Hole Knockouts




**11W LED BULKHEADS**

Robustly constructed, reliable wall fitting offering more discreet illumination for utility applications

- Tough polycarbonate housing
- Hinged diffuser
- Opal diffuser: evenly diffused light output
- Corrosion resistant stainless steel cover fixing screws
- Cable channel on reverse of fitting with 20mm knockout conduit entries

**BULKLEDPC:** Integral photocell: automatic dusk to dawn operation

| Code      | Version   | Wattage | Colour Temp. | Lumens | Avg. Rated Life (Hrs) | IP Rating | MOM / OPQ |
|-----------|-----------|---------|--------------|--------|-----------------------|-----------|-----------|
| BULKLED   | Standard  | 11.2W   | 6500K        | 900 lm | 30,000 hrs            | IP65      | 1 / 12    |
| BULKLEDPC | Photocell |         |              |        |                       |           |           |



| LED LAMP SPECIFICATIONS:                                 |                               |
|--|-------------------------------|
| Luminaire Lumens (with diffuser)                         | <b>900 lm</b>                 |
| Lumens From Chip (no diffuser)                           | <b>1400 lm</b>                |
| Rated Wattage  | 11.2W                         |
| Rated luminous flux                                      | 900 lm                        |
| Nominal life time of the lamp                            | 30,000 hrs                    |
| Colour temperature                                       | 6500K                         |
| Number of switching cycles before premature lamp failure | ≥15,000                       |
| Warm-up time up to 60 % of the full light output         | Instant full light            |
| Dimmable   | No                            |
| LED array dimensions (L/W)                               | 140 x130mm                    |
| Nominal beam angle                                       | 120°                          |
| Rated power  | 11.2W                         |
| Rated lamp lifetime                                      | 30,000 hrs                    |
| Displacement factor                                      |                               |
| Lumen maintenance factor at end of nominal life          | >80%                          |
| Starting time  | <0.5s                         |
| Colour rendering   | ≥80                           |
| Colour consistency                                       | Within 6 step Macadam ellipse |
| Rated peak intensity                                     | 230cd                         |
| Rated beam angle   | 120°                          |
| Voltage  | 240V                          |
| Not suitable for accent lighting                         |                               |