## **DATASHEET**



**Code:** HM2078

**Verve | Connection Units** 

## Product Image



١/	١,		r	ı	n	
v	v	ı		ı		q



## **Dimensions**



## Dimensional drawing is not available

Insert Type	1 gang 25A Cable Outlet			
Insert Colour	White			
EAN13 Barcode	5052750550439			
Commodity Code	85369095			
Luckins TSI	434148334			
Dimensions(Nominal)	Single: Height = 86.7mm Width = 86.7mm Depth = 10.0mm			
Weight	85 GR			
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A			
Switched Poles	Single			
Current Rating	25 Amp			
Voltage	220/250V AC			
Maximum Load	25 Amp			
Contact Gap Minimum	3mm			
Terminal Capacity 1	3x2.5mm²			
Terminal Capacity 2	2x4mm² Multi-strand			
Terminal Capacity 3	1x6mm²			
Terminal Capacity 4	6 x1mm²			
Earth Terminal Capacity 1	5x1.5mm²			
Earth Terminal Capacity 2	3 x 2.5mm²			
Earth Terminal Capacity 3	2 x 4mm²			
Earth Terminal Capacity 4	1 x 6mm²			
Product Class 1	Must be earthed			
Ambient Operating Temperature	-5° to +40°C			
Recommended Location	Internal Use Only			
Maximum Installation Altitude	2000m			
Standard/Approval	BS EN 1363-4			

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

**E:** info@hamilton-litestat.com | **W:** www.hamilton-litestat.com

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. This datasheet was expected on 5/9/20/32 2:38:09 PM ESOE