



## PRODUCT-DETAILS

# AF16-30-10-14

## AF16-30-10-14 250-500V50/60HZ-DC Contactor

### General Information

|                       |                                            |
|-----------------------|--------------------------------------------|
| Extended Product Type | AF16-30-10-14                              |
| Product ID            | 1SBL177001R1410                            |
| EAN                   | 3471523110649                              |
| Catalog Description   | AF16-30-10-14 250-500V50/60HZ-DC Contactor |

#### Long Description

The AF16-30-10-14 is a 3 pole - 690 V IEC or 600 UL contactor with 1 built-in auxiliary contact and screw terminals, controlling motors up to 7.5 kW / 400 V AC (AC-3) or 10 hp / 480 V UL and switching power circuits up to 30 A (AC-1) or 30 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (250-500 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.

### Ordering

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85364900 |

### Popular Downloads

|                          |                 |
|--------------------------|-----------------|
| Instructions and Manuals | 1SBC101027M6801 |
|--------------------------|-----------------|

CAD Dimensional  
Drawing

2CDC001079B0201

## Dimensions

|                               |         |
|-------------------------------|---------|
| Product Net Width             | 45 mm   |
| Product Net Depth /<br>Length | 77 mm   |
| Product Net Height            | 86 mm   |
| Product Net Weight            | 0.31 kg |

## Technical

|                                                       |                                                                                                                                                      |
|-------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of Main Contacts<br>NO                         | 3                                                                                                                                                    |
| Number of Main Contacts<br>NC                         | 0                                                                                                                                                    |
| Number of Auxiliary<br>Contacts NO                    | 1                                                                                                                                                    |
| Number of Auxiliary<br>Contacts NC                    | 0                                                                                                                                                    |
| Standards                                             | IEC 60947-1 / 60947-4-1 and EN 60947-1 / 60947-4-16, UL 60947-4-1, CSA<br>C22.2 No. 60947-4-1                                                        |
| Rated Operational Voltage                             | Auxiliary Circuit 690 V<br>Main Circuit 690 V                                                                                                        |
| Rated Frequency (f)                                   | Auxiliary Circuit 50 / 60 Hz<br>Control Circuit 50 / 60 Hz<br>Main Circuit 50 / 60 Hz                                                                |
| Conventional Free-air<br>Thermal Current ( $I_{th}$ ) | acc. to IEC 60947-4-1, Open Contactors $\Theta = 40^\circ\text{C}$ 35 A<br>acc. to IEC 60947-5-1, $\Theta = 40^\circ\text{C}$ 16 A                   |
| Rated Operational Current<br>AC-1 ( $I_e$ )           | (690 V) 40 °C 30 A<br>(690 V) 60 °C 30 A<br>(690 V) 70 °C 26 A                                                                                       |
| Rated Operational Current<br>AC-3 ( $I_e$ )           | (415 V) 60 °C 18 A<br>(440 V) 60 °C 18 A<br>(500 V) 60 °C 15 A<br>(690 V) 60 °C 10.5 A<br>(380 / 400 V) 60 °C 18 A<br>(220 / 230 / 240 V) 60 °C 18 A |
| Rated Operational Current<br>AC-3e ( $I_e$ )          | (415 V) 60 °C 18 A<br>(440 V) 60 °C 18 A<br>(500 V) 60 °C 15 A<br>(690 V) 60 °C 10.5 A<br>(380 / 400 V) 60 °C 18 A<br>(220 / 230 / 240 V) 60 °C 18 A |
| Rated Operational Power<br>AC-3 ( $P_e$ )             | (400 V) 7.5 kW<br>(415 V) 9 kW<br>(440 V) 9 kW<br>(500 V) 9 kW<br>(690 V) 9 kW<br>(380 / 400 V) 7.5 kW<br>(220 / 230 / 240 V) 4 kW                   |
| Rated Operational Power<br>AC-3e ( $P_e$ )            | (415 V) 9 kW<br>(440 V) 9 kW<br>(500 V) 9 kW<br>(690 V) 9 kW<br>(380 / 400 V) 7.5 kW                                                                 |

|                                        |                                                                   |
|----------------------------------------|-------------------------------------------------------------------|
|                                        | (220 / 230 / 240 V) 4 kW                                          |
| Rated Operational Current              | (500 V) 2 A                                                       |
| AC-15 ( $I_e$ )                        | (690 V) 2 A                                                       |
|                                        | (24 / 127 V) 6 A                                                  |
|                                        | (220 / 240 V) 4 A                                                 |
|                                        | (400 / 440 V) 3 A                                                 |
| Rated Short-time                       | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 150 A  |
| Withstand Current Low                  | at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 35 A |
| Voltage ( $I_{cw}$ )                   | at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 60 A  |
|                                        | at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 300 A   |
|                                        | at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 80 A   |
|                                        | for 0.1 s 140 A                                                   |
|                                        | for 1 s 100 A                                                     |
| Maximum Breaking Capacity              | cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 250 A      |
|                                        | cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 106 A      |
| Maximum Electrical Switching Frequency | (AC-1) 600 cycles per hour                                        |
|                                        | (AC-15) 1200 cycles per hour                                      |
|                                        | (AC-2 / AC-4) 300 cycles per hour                                 |
|                                        | (AC-3) 1200 cycles per hour                                       |
|                                        | (DC-13) 900 cycles per hour                                       |
| Rated Operational Current              | (110 V) 1-Pole, 40 °C 20 A                                        |
| DC-1 ( $I_e$ )                         | (110 V) 1-Pole, 60 °C 20 A                                        |
|                                        | (110 V) 1-Pole, 70 °C 20 A                                        |
|                                        | (110 V) 2 Poles in Series, 40 °C 30 A                             |
|                                        | (110 V) 2 Poles in Series, 60 °C 30 A                             |
|                                        | (110 V) 2 Poles in Series, 70 °C 26 A                             |
|                                        | (110 V) 3 Poles in Series, 40 °C 30 A                             |
|                                        | (110 V) 3 Poles in Series, 60 °C 30 A                             |
|                                        | (110 V) 3 Poles in Series, 70 °C 26 A                             |
|                                        | (220 V) 2 Poles in Series, 40 °C 20 A                             |
|                                        | (220 V) 2 Poles in Series, 60 °C 20 A                             |
|                                        | (220 V) 2 Poles in Series, 70 °C 20 A                             |
|                                        | (220 V) 3 Poles in Series, 40 °C 30 A                             |
|                                        | (220 V) 3 Poles in Series, 60 °C 30 A                             |
|                                        | (220 V) 3 Poles in Series, 70 °C 26 A                             |
|                                        | (72 V) 1-Pole, 40 °C 30 A                                         |
|                                        | (72 V) 1-Pole, 60 °C 30 A                                         |
|                                        | (72 V) 1-Pole, 70 °C 26 A                                         |
|                                        | (72 V) 2 Poles in Series, 40 °C 30 A                              |
|                                        | (72 V) 2 Poles in Series, 60 °C 30 A                              |
|                                        | (72 V) 2 Poles in Series, 70 °C 26 A                              |
|                                        | (72 V) 3 Poles in Series, 40 °C 30 A                              |
|                                        | (72 V) 3 Poles in Series, 60 °C 30 A                              |
|                                        | (72 V) 3 Poles in Series, 70 °C 26 A                              |
| Rated Operational Current              | (110 V) 1-Pole, 40 °C 8 A                                         |
| DC-3 ( $I_e$ )                         | (110 V) 1-Pole, 60 °C 8 A                                         |
|                                        | (110 V) 1-Pole, 70 °C 8 A                                         |
|                                        | (110 V) 2 Poles in Series, 40 °C 30 A                             |
|                                        | (110 V) 2 Poles in Series, 60 °C 30 A                             |
|                                        | (110 V) 2 Poles in Series, 70 °C 26 A                             |
|                                        | (110 V) 3 Poles in Series, 40 °C 30 A                             |
|                                        | (110 V) 3 Poles in Series, 60 °C 30 A                             |
|                                        | (110 V) 3 Poles in Series, 70 °C 26 A                             |
|                                        | (220 V) 2 Poles in Series, 40 °C 8 A                              |
|                                        | (220 V) 2 Poles in Series, 60 °C 8 A                              |
|                                        | (220 V) 2 Poles in Series, 70 °C 8 A                              |
|                                        | (220 V) 3 Poles in Series, 40 °C 30 A                             |
|                                        | (220 V) 3 Poles in Series, 60 °C 30 A                             |
|                                        | (220 V) 3 Poles in Series, 70 °C 26 A                             |
|                                        | (72 V) 1-Pole, 40 °C 30 A                                         |
|                                        | (72 V) 1-Pole, 60 °C 30 A                                         |
|                                        | (72 V) 1-Pole, 70 °C 26 A                                         |
|                                        | (72 V) 2 Poles in Series, 40 °C 30 A                              |
|                                        | (72 V) 2 Poles in Series, 60 °C 30 A                              |
|                                        | (72 V) 2 Poles in Series, 70 °C 26 A                              |
|                                        | (72 V) 3 Poles in Series, 40 °C 30 A                              |
|                                        | (72 V) 3 Poles in Series, 60 °C 30 A                              |
|                                        | (72 V) 3 Poles in Series, 70 °C 26 A                              |

|                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|--------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                  | (72 V) 3 Poles in Series, 70 °C 26 A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Rated Operational Current<br>DC-5 ( $I_e$ )      | (110 V) 1-Pole, 40 °C 4 A<br>(110 V) 1-Pole, 60 °C 4 A<br>(110 V) 1-Pole, 70 °C 4 A<br>(110 V) 2 Poles in Series, 40 °C 20 A<br>(110 V) 2 Poles in Series, 60 °C 20 A<br>(110 V) 2 Poles in Series, 70 °C 20 A<br>(110 V) 3 Poles in Series, 40 °C 30 A<br>(110 V) 3 Poles in Series, 60 °C 30 A<br>(110 V) 3 Poles in Series, 70 °C 26 A<br>(220 V) 2 Poles in Series, 40 °C 4 A<br>(220 V) 2 Poles in Series, 60 °C 4 A<br>(220 V) 2 Poles in Series, 70 °C 4 A<br>(220 V) 3 Poles in Series, 40 °C 16 A<br>(220 V) 3 Poles in Series, 60 °C 16 A<br>(220 V) 3 Poles in Series, 70 °C 16 A<br>(72 V) 1-Pole, 40 °C 16 A<br>(72 V) 1-Pole, 60 °C 16 A<br>(72 V) 1-Pole, 70 °C 16 A<br>(72 V) 2 Poles in Series, 40 °C 30 A<br>(72 V) 2 Poles in Series, 60 °C 30 A<br>(72 V) 2 Poles in Series, 70 °C 26 A<br>(72 V) 3 Poles in Series, 40 °C 30 A<br>(72 V) 3 Poles in Series, 60 °C 30 A<br>(72 V) 3 Poles in Series, 70 °C 26 A |
| Rated Operational Current<br>DC-13 ( $I_e$ )     | (24 V) 6 A / 144 W<br>(48 V) 2.8 A / 134 W<br>(72 V) 1 A / 72 W<br>(110 V) 0.55 A / 60 W<br>(125 V) 0.55 A / 69 W<br>(220 V) 0.27 A / 60 W<br>(250 V) 0.27 A / 68 W<br>(400 V) 0.15 A / 60 W<br>(500 V) 0.13 A / 65 W<br>(600 V) 0.1 A / 60 W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Rated Insulation Voltage<br>( $U_i$ )            | acc. to IEC 60947-4-1 690 V<br>acc. to IEC 60947-5-1 690 V<br>acc. to UL/CSA 600 V                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Rated Impulse Withstand<br>Voltage ( $U_{imp}$ ) | 6 kV                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Maximum Mechanical<br>Switching Frequency        | 3600 cycles per hour                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Rated Control Circuit<br>Voltage ( $U_c$ )       | 50 Hz 250 ... 500 V<br>60 Hz 250 ... 500 V<br>DC Operation 250 ... 500 V                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Operate Time                                     | Between Coil De-energization and NC Contact Closing 13 ... 98 ms<br>Between Coil De-energization and NO Contact Opening 11 ... 95 ms<br>Between Coil Energization and NC Contact Opening 38 ... 90 ms<br>Between Coil Energization and NO Contact Closing 40 ... 95 ms                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Mounting on DIN Rail                             | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715<br>TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Mounting by Screws (not<br>supplied)             | 2 x M4 screws placed diagonally                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Connecting Capacity Main<br>Circuit              | Flexible with Ferrule 1/2x 0.75 ... 6 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 4 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm <sup>2</sup><br>Rigid Solid 1/2x 1 ... 4 mm <sup>2</sup><br>Rigid Stranded 1/2x 1 ... 6 mm <sup>2</sup>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Connecting Capacity<br>Auxiliary Circuit         | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Rigid Solid 1/2x 1 ... 2.5 mm <sup>2</sup><br>Rigid Stranded 1/2x 1 ... 2.5 mm <sup>2</sup>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Connecting Capacity                              | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

|                       |                                                                                                                                                                                                                                   |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Control Circuit       | Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Rigid Solid 1/2x 1 ... 2.5 mm <sup>2</sup><br>Rigid Stranded 1/2x 1 ... 2.5 mm <sup>2</sup> |
| Wire Stripping Length | Auxiliary Circuit 10 mm<br>Control Circuit 10 mm<br>Main Circuit 10 mm                                                                                                                                                            |
| Degree of Protection  | acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20<br>acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20<br>acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20                                 |
| Terminal Type         | Screw Terminals                                                                                                                                                                                                                   |

## Technical UL/CSA

|                                                 |                                                                                                                                                                                                                                |
|-------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General Use Rating<br>UL/CSA                    | (600 V AC) 30 A                                                                                                                                                                                                                |
| Horsepower Rating<br>UL/CSA                     | (120 V AC) Single Phase 1-1/2 hp<br>(200 ... 208 V AC) Three Phase 5 hp<br>(220 ... 240 V AC) Three Phase 5 hp<br>(240 V AC) Single Phase 3 hp<br>(440 ... 480 V AC) Three Phase 10 hp<br>(550 ... 600 V AC) Three Phase 15 hp |
| Connecting Capacity Main<br>Circuit UL/CSA      | Rigid Solid 1/2x 16-10 AWG<br>Rigid Stranded 1/2x 16-10 AWG                                                                                                                                                                    |
| Connecting Capacity<br>Auxiliary Circuit UL/CSA | Rigid Solid 1/2x 18-14 AWG<br>Rigid Stranded 1/2x 18-14 AWG                                                                                                                                                                    |
| Connecting Capacity<br>Control Circuit UL/CSA   | Rigid Solid 1/2x 18-14 AWG<br>Rigid Stranded 1/2x 18-14 AWG                                                                                                                                                                    |
| Tightening Torque<br>UL/CSA                     | Auxiliary Circuit 11 in-lb<br>Control Circuit 11 in-lb<br>Main Circuit 13 in-lb                                                                                                                                                |

## Environmental

|                                                   |                                                                                                                                                                                  |
|---------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ambient Air Temperature                           | Close to Contactor Fitted with Thermal O/L Relay -25 ... 60 °C<br>Close to Contactor without Thermal O/L Relay -40 ... 70 °C<br>Close to Contactor for Storage -60 ... +80 °C    |
| Climatic Withstand                                | Category B according to IEC 60947-1 Annex Q                                                                                                                                      |
| Maximum Operating<br>Altitude Permissible         | Without Derating 3000 m                                                                                                                                                          |
| Resistance to Vibrations<br>acc. to IEC 60068-2-6 | 5 ... 300 Hz 4 g closed position / 2 g open position                                                                                                                             |
| Resistance to Shock acc.<br>to IEC 60068-2-27     | Closed, Shock Direction: B1 25 g<br>Open, Shock Direction: B1 5 g<br>Shock Direction: A 30 g<br>Shock Direction: B2 15 g<br>Shock Direction: C1 25 g<br>Shock Direction: C2 25 g |
| RoHS Status                                       | Following EU Directive 2011/65/EU                                                                                                                                                |

## Certificates and Declarations (Document Number)

|                 |                    |
|-----------------|--------------------|
| ABS Certificate | ABS_20-2060694-PDA |
| BV Certificate  | BV_2634H24898B0    |
| CB Certificate  | CB_SE-108879       |

|                                     |                                            |
|-------------------------------------|--------------------------------------------|
| CCC Certificate                     | CCC_2010010304445624                       |
| CQC Certificate                     | CQC2010010304445624<br>CQC2020010304298240 |
| Declaration of Conformity<br>- CCC  | 2020980304001253<br>2020980304001082       |
| Declaration of Conformity<br>- CE   | 1SBD250000U1000                            |
| Declaration of Conformity<br>- UKCA | 1SBD250031U1000                            |
| EAC Certificate                     | EAC_RU_FRME77B03447                        |
| Environmental Information           | 1SBD250147E1000<br>1SBC100222M0201         |
| GL Certificate                      | DNV-GL_TAE00001AF-3                        |
| GOST Certificate                    | GOST_POCCFR.ME77.B07175.pdf                |
| Instructions and Manuals            | 1SBC101027M6801                            |
| KC Certificate                      | KC_HW02016-15005C                          |
| LR Certificate                      | LRS_1300087E1                              |
| REACH Declaration                   | 2CMT2021-006202                            |
| RINA Certificate                    | RINA_ELE240318XG                           |
| RMRS Certificate                    | RMRS_1802705280                            |
| RoHS Information                    | 2CMT2021-006277                            |
| UL Certificate                      | UL-US-2150887-5<br>UL-CA-2142658-5         |
| UL Listing Card                     | E312527                                    |

## Container Information

|                                   |               |
|-----------------------------------|---------------|
| Package Level 1 Units             | box 1 piece   |
| Package Level 1 Width             | 87 mm         |
| Package Level 1 Depth /<br>Length | 79 mm         |
| Package Level 1 Height            | 47 mm         |
| Package Level 1 Gross<br>Weight   | 0.31 kg       |
| Package Level 1 EAN               | 3471523110649 |
| Package Level 2 Units             | box 27 piece  |
| Package Level 2 Width             | 250 mm        |
| Package Level 2 Depth /<br>Length | 300 mm        |
| Package Level 2 Height            | 315 mm        |
| Package Level 2 Gross<br>Weight   | 8.37 kg       |
| Package Level 3 Units             | 1296 piece    |

## Classifications

|                            |                                           |
|----------------------------|-------------------------------------------|
| Object Classification Code | Q                                         |
| ETIM 4                     | EC000066 - Magnet contactor, AC-switching |
| ETIM 5                     | EC000066 - Magnet contactor, AC-switching |

|                                    |                                          |
|------------------------------------|------------------------------------------|
| ETIM 6                             | EC000066 - Power contactor, AC switching |
| ETIM 7                             | EC000066 - Power contactor, AC switching |
| ETIM 8                             | EC000066 - Power contactor, AC switching |
| eClass                             | V11.0 : 27371003                         |
| UNSPSC                             | 39121529                                 |
| IDEA Granular Category Code (IGCC) | 4758 >> Iec Contactors                   |
| E-Number (Finland)                 | 3706244                                  |
| E-Number (Sweden)                  | 3211374                                  |

---

### Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors