
PRODUCT-DETAILS

CA3-10

CA3-10 Auxiliary Contact Block

General Information

Extended Product Type	CA3-10
Product ID	1SBN011010T1010
EAN	3471523095007
Catalog Description	CA3-10 Auxiliary Contact Block
Long Description	CA3-10 Auxiliary Contact Block

Ordering

Minimum Order Quantity	10 piece
Customs Tariff Number	85389099
Product Main Type	Accessories for Block Contactors

Popular Downloads

Instructions and Manuals	1SBC101020M9701
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	44.2 mm
Product Net Depth / Length	9.5 mm
Product Net Height	33.5 mm
Product Net Weight	0.011 kg

Technical

Connecting Capacity	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ²
Auxiliary Circuit	Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ²
	Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ²
	Rigid 1/2x 0.75 ... 2.5 mm ²
Connecting Capacity	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ²
Control Circuit	Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ²
	Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ²
	Rigid 1/2x 0.75 ... 2.5 mm ²
Maximum Electrical Switching Frequency	(AC-15) 1200 cycles per hour (DC-13) 900 cycles per hour
Maximum Mechanical Switching Frequency	3600 cycles per hour
Number of Auxiliary Contacts NC	0
Number of Auxiliary Contacts NO	1
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz
Rated Insulation Voltage (U _i)	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V acc. to UL/CSA 600 V
Rated Operational Current AC-15 (I _e)	(500 V) NC 2 (500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (400 / 440 V) 3 A
Rated Operational Current DC-13 (I _e)	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W
Rated Operational Voltage	Auxiliary Circuit 690 V Main Circuit 690 V
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 0.1 s 140 A for 1 s 100 A
Suitable For	AS09 AS12 AS16 ASL09 ASL12 ASL16 VAS09 VAS12 VAS16 VASL09 VASL12 VASL16

NS
NSL

Terminal Type	Screw Terminals
Tightening Torque	Auxiliary Circuit 1 N·m
Wire Stripping Length	Auxiliary Circuit 9 mm

Technical UL/CSA

Tightening Torque UL/CSA	Auxiliary Circuit 9 in·lb
-----------------------------	---------------------------

Environmental

Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-5-1, $\Theta = 40\text{ }^{\circ}\text{C}$ 10 A
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
RoHS Information	2CMT2021-006277
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations (Document Number)

CB Certificate	CB_CN_32922
CCC Certificate	CCC_2007010305252103
CQC Certificate	CQC2007010305252103
Declaration of Conformity - CCC	2020980305001186
Declaration of Conformity - CE	1SBD250017U1000
Declaration of Conformity - UKCA	1SBD250052U1000
Environmental Information	1SBD250133E1001
GOST Certificate	GOST_POCCCNME77B07822.pdf
Instructions and Manuals	1SBC101020M9701
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
UL Certificate	UL_220108-E312527A
UL Listing Card	NOA_E312527.pdf

Container Information

Package Level 1 Units	10 piece
Package Level 1 Width	130 mm
Package Level 1 Depth / Length	45 mm
Package Level 1 Height	64 mm
Package Level 1 Gross Weight	0.11 kg

Package Level 1 EAN	3471523095007
Package Level 2 Units	400 piece
Package Level 2 Width	270 mm
Package Level 2 Depth / Length	360 mm
Package Level 2 Height	220 mm
Package Level 2 Gross Weight	4.6 kg

Classifications

eClass	V11.0 : 27371302
E-Number (Sweden)	3210519
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
ETIM 8	EC000041 - Auxiliary contact block
ETIM 9	EC000041 - Auxiliary contact block
IDEA Granular Category Code (IGCC)	4743 >> Auxiliary contact block
Object Classification Code	K
UNSPSC	39121522

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors Accessories