

## DCD796P2-GB

#### 18V XR Brushless Hammer Drill Driver - 2 X 5Ah

### **Selling Propositions**

- 15 position adjustable torque control for consistent screw driving into a variety of materials
- Ergonomic design with rubber grip over-mould improving users comfort
- Intelligent trigger design allows for total control of application
- · Two speed all metal transmission for increased runtime and longer tool life
- · Ultra compact, lightweight design allows use in confined spaces
- Steel belt hook and magnetic bit holder ensures strong storage solutions
- · Brushless Motor Technology for excellent efficiency
- Part of the intelligent XR Series designed for efficiency and making applications faster

### **Standard Equipment**

- Belt hook (1)
- Magnetic bit holder (1)
- 5Ah XR battery packs with state of charge indicator (2)
  - Multi-voltage XR charger (1)
  - TSTAK heavy duty kitbox (1)

# **Warranty specifications**

• DEWALT 3 year European PT Guarantee (subject to registration)

Specifications	
Max. Drilling Capacity [Wood]	40.0 mm
Max. Drilling Capacity [Metal]	13.0 mm
Max. Drilling Capacity [Masonry]	13.0 mm
Max Torque (Hard)	70.0 Nm
No Load Speed (Drilling/ Driving Mode)	0-550/2000 rpm
Beats per Minute	0-9350/34000 bpm
No Load Speed (Hammer Mode)	0-550/2000 rpm
Battery Capacity	5.0 Ah
Battery Chemistry	Li-lon
Power Output	420.0 W
Max Torque (Soft)	27.0 Nm
Chuck capacity	1.5-13 mm
No. of Speeds	2.0
Weight	1.3 kg
Weight (incl. battery)	1.9 mm
Length	173.0 mm
Height	203.0 mm
Depth	67.0 mm
Sound Pressure	89.0 dB(A)
Sound Pressure Uncertainty	3.0 dB(A)
Sound Power	100.0 dB(A)
Sound Power Uncertainty	3.0 dB(A)
Hand/Arm Vibration - Drilling into metal	<2.5 m/s <sup>2</sup>
Uncertainty K 1 (Vibration)	1.5 m/s <sup>2</sup>
Hand/Arm Vibration - Hammer drilling into	11.5 m/s <sup>2</sup>
concrete	
Uncertainty K 2 (Vibration)	1.6 m/s <sup>2</sup>
Hand/Arm Vibration - Screw driving without	<2.5 m/s <sup>2</sup>
impact	1.5 / 0
Uncertainty K 3 (Vibration)	1.5 m/s <sup>2</sup>

