

# DCS380N-XJ

### 18V XR Reciprocating Saw - Bare Unit



## **Selling Propositions**

- Improved ergonomic design
- Lever-action keyless blade clamp for quick and easy blade changes
- · Four-position blade clamp allows for flush cutting and increased versatility
- Pivoting adjustable shoe with open top for high stability and blade visibility during a cut
- Intelligent variable speed trigger, lock-off switch and electronic motor brake for quick controlled cuts and enhanced work safety

### **Standard Equipment**

• Battery and charger sold separately (1)

### **Warranty specifications**

• DEWALT 3 year European PT Guarantee (subject to registration)

Specifications	
No Load Stroke Rate	0-2950 spm
Max. Cutting Capacity (Wood)	300.0 mm
Max. Cutting Capacity (Steel Section and Pipes)	130.0 mm
Max. Cutting Capacity [PVC]	160.0 mm
Weight	2.7 kg
Power Output	560 W
Length	425.0 mm
Height	195.0 mm
Sound Pressure	88.0 dB(A)
Sound Pressure Uncertainty	3.0 dB(A)
Sound Power	99.0 dB(A)
Sound Power Uncertainty	3.0 dB(A)
Uncertainty K 1 (Vibration)	6.3 m/s <sup>2</sup>
Hand/Arm Vibration - Cutting boards	31 m/s <sup>2</sup>
Uncertainty K 2 (Vibration)	8.1 m/s <sup>2</sup>
Hand/Arm Vibration - Cutting wooden beams	33.0 m/s <sup>2</sup>
Uncertainty K 3 (Vibration)	6.6 m/s <sup>2</sup>