



Ledinaire Waterproof WT065C

WT065C LED84S/840 PSU L1800

- 840 neutral white - Power supply unit (ON/OFF)

The Ledinaire Waterproof range provides maximum performance and durability at great value. As an off-the-shelf LED luminaire solution for all your everyday needs, it can be deployed in a wide variety of locations.

Product data

General Information	
Light source replaceable	No
Number of gear units	1 unit
Driver included	Yes
Feed-through wiring	Simple Connection and removable cover available for feed-through wiring 1-phase (internal wiring is not included)
Service tag	No
Lighting Technology	LED
Value ladder	Value
Light Technical	
Luminous Flux	8,400 lumen
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	129 lm/W
Color rendering index (CRI)	>80
Flickering value (PstLM)	1
Stroboscopic effect value (SVM)	1.6
Beam angle of light source	120 degree(s)

Light source color	840 neutral white
Optic type	Symmetrical
Luminaire light beam spread	120°
Unified glare rating CEN	Not applicable
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Input Frequency	50 or 60 Hz
Initial CLO power consumption	- W
Average CLO power consumption	- W
Power Consumption	65 W
Inrush current	29.7 A
Inrush time	0.0825 ms
Power Factor (Fraction)	0.9
Connection	Connection unit 3-pole
Cable	-
Number of products on MCB of 16 A type B	18


Ledinaire Waterproof WT065C

Temperature	
Ambient temperature range	-20 to +40 °C
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (ON/OFF)
Control interface	-
Constant light output	No
Mechanical and Housing	
Housing Material	Polycarbonate
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Stainless steel
Housing Color	Gray and white
Optical cover/lens finish	Opal
Overall length	1,870 mm
Overall width	97 mm
Overall height	83 mm
Dimensions (Height x Width x Depth)	83 x 97 x 1870 mm
Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Sustainability rating	-
Protection class IEC	Safety class I
Glow-wire test	Temperature 850 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes

ENEC mark	-
Warranty period	3 years
EU RoHS compliant	Yes
Initial Performance (IEC Compliant)	
Luminous flux tolerance	-10%,+15%
Initial chromaticity	<5
Power consumption tolerance	+/-10%
Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life 50000 h	0.075 %
Lumen maintenance at median useful life* 50000 h	L65
Application Conditions	
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Yes
Product Data	
Full product code	871016336956399
Order product name	WT065C LED84S/840 PSU L1800
Order code	911401825781
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material number (12NC)	911401825781
Full product name	WT065C LED84S/840 PSU L1800
EAN/UPC - Case	8710163369624



Dimensional drawing



Ledinaire Waterproof WT065C

