



Ledinaire Batten BN065C

BN065C LED25S/840 PSU L1200 UKI

- 840 neutral white

The Ledinaire Batten range provides maximum performance and versatility at great value. As an off-the-shelf LED luminaire solution for all your everyday needs, it can be deployed in a wide variety of locations.

Product data

General Information		Operating and Electrical	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	Optic type	Very wide beam
Light source replaceable	No	Luminaire light beam spread	130°
Number of gear units	1 unit	Unified glare rating CEN	27
Driver included	Yes	Operating and Electrical	
Feed-through wiring	Simple Connection and removable cover available for feed-through wiring 1-phase (internal wiring is not included)	Input Voltage	220 to 240 V
Service tag	No	Line Frequency	50 or 60 Hz
Lighting Technology	LED	Input Frequency	50 or 60 Hz
Light Technical		Initial CLO power consumption	- W
Luminous Flux	2,500 lumen	Average CLO power consumption	- W
Saturated Red (R9)	<50	Power Consumption	22.5 W
Correlated Color Temperature (Nom)	4000 K	Inrush current	2.96 A
Luminous Efficacy (rated) (Nom)	109 lm/W	Inrush time	0.0941 ms
Color rendering index (CRI)	>80	Power Factor (Fraction)	0.9
Beam angle of light source	- degree(s)	Connection	Push-in connector 3-pole
Light source color	840 neutral white	Cable	-
		Number of products on MCB of 16 A type B	78


Ledinaire Batten BN065C

Temperature	
Ambient temperature range	-20 to +40 °C
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (ON/OFF)
Control interface	-
Constant light output	No
Mechanical and Housing	
Housing Material	Steel
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	-
Housing Color	White
Optical cover/lens finish	Opal
Overall length	1,135 mm
Overall width	65 mm
Overall height	65 mm
Dimensions (Height x Width x Depth)	65 x 65 x 1135 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK04 [0.5 J standard plus]
Sustainability rating	-
Protection class IEC	Safety class I
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	-
CE mark	Yes
ENEC mark	-

Warranty period	3 years
EU RoHS compliant	Yes
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.38,0.38)SDCM<5
Power consumption tolerance	+/-10%
Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life 50000 h	7.5 %
Lumen maintenance at median useful life* 50000 h	L65
Application Conditions	
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Not applicable
Product Data	
Full product code	871016336963199
Order product name	BN065C LED25S/840 PSU L1200 UKI
Order code	911401825881
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	8
Material number (12NC)	911401825881
Full product name	BN065C LED25S/840 PSU L1200 UKI
EAN/UPC - Case	8710163369693



Dimensional drawing



Ledinaire Batten BN065C

