



Data Sheet

Product Code: FQP1M1W

This product can also be made using our Matrix System, using the products WQ1W + MFP1M1 x 1

Product Description: 1-Gang 2-Way Dimmer for Multiple HF Ballasts/LED Drivers requiring 1-10V DC Input

Range: White

Finish: White Plastic

Product Category: 1-10V Dimmers

Insert/Knob Colour: White Knob

Barcode: 5021575581942

Dimensions: 85x85x46mm

Faceplate Depth: 11mm

Net Weight: 116g

Gross Weight: 118g

Fixing Centres: 60.3mm

Depth from Mounting Face: 15.3mm

Recommended Back Box Depth: 25mm

Operating Voltage: 230v 50Hz (Switching), 1-10V DC Dimming Control Signal

Maximum Load Rating: 6A (Switching) 20mA (Dimming Control Signal)

Maximum Current Rating: 6A (Switching) 20mA (Dimming Control Signal)

Terminal (Live) Diameter: 3.2mm; **Capacity:** 3 x 1.5mm²

Intended Applications: Indoor Use Only. Domestic lighting circuits.

Safety Advice: For use with 1-1V ballasts/drivers only. Check the in-rush current for LED bulbs or drivers does not exceed 6A, and the rating on the control signal side of the ballast/driver does not exceed 2mA before connecting. Fit inrush current limiters where necessary. Do not overload.

Applicable Safety Standard: BS EN 60669-2-1



Product Features

- ⊙ V-Dim dimming technology
- ⊙ Designed to work with one or multiple dimmable ballasts up to 20mA
- ⊙ Durable white plastic



10 YEAR GUARANTEE

BRITISH MADE



Commodity Code: 85365015

Declaration of Conformity

All information is subject to change without notice. Errors and omissions excepted. Images are for illustrative purposes only. Individual features and colours may vary. Refer to date of issue to identify latest version.

Date of Issue: 24th May 2023 © Doyle & Tratt Products Ltd, Carylls Lea, Faygate, West Sussex, RH12 4SJ, United Kingdom. All rights reserved.